



## Commercial status

Discontinued: 01 January 2017

End-of-service: 01 January 2025

has not been replaced. Please contact your customer care center for more information.

⚠ Discontinued

## Main

|                                   |  |
|-----------------------------------|--|
| Range of product                  | Altivar 61   |
| Product or component type         | Variable speed drive   |
| Product specific application      | Pumping and ventilation machine  |
| Component name                    | ATV61  |
| Motor power kW                    | 280 kW, 3 phases at 380...480 V<br>315 kW, 3 phases at 380...480 V   |
| Motor power hp                    | 450 hp, 3 phases at 380...480 V<br>500 hp, 3 phases at 380...480 V   |
| Power supply voltage              | 380...480 V - 15...10 %  |
| Supply number of phases           | 3 phases   |
| Line current                      | 494 A for 380 V 3 phases 280 kW / 450 hp<br>494 A for 480 V 3 phases 280 kW / 450 hp<br>544 A for 480 V 3 phases 315 kW / 500 hp<br>555 A for 380 V 3 phases 315 kW / 500 hp     |
| EMC filter                        | Level 3 EMC filter   |
| Variant                           | Without DC choke   |
| Assembly style                    | With heat sink   |
| Apparent power                    | 325.1 kVA at 380 V 3 phases 280 kW / 450 hp<br>365.3 kVA at 380 V 3 phases 315 kW / 500 hp   |
| Maximum prospective line Isc      | 50 kA for 3 phases   |
| Maximum transient current         | 739.2 A for 60 s, 3 phases   |
| Nominal switching frequency       | 2.5 kHz  |
| Switching frequency               | 2...8 kHz adjustable<br>2.5...8 kHz with derating factor   |
| Asynchronous motor control        | Voltage/frequency ratio, 2 points<br>Flux vector control without sensor, standard<br>Voltage/frequency ratio, 5 points<br>Voltage/frequency ratio - Energy Saving, quadratic U/f |
| Synchronous motor control profile | Vector control without sensor, standard  |
| Communication port protocol       | CANopen<br>Modbus  |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                      |   |
|----------------------|---|
| Type of polarization | No impedance for Modbus   |
| Option card          | Communication card for APOGEE FLN<br>Communication card for BACnet<br>Communication card for CC-Link<br>Controller inside programmable card<br>Communication card for DeviceNet<br>Communication card for Ethernet/IP<br>Communication card for Fipio<br>I/O extension card<br>Communication card for Interbus-S<br>Communication card for LonWorks<br>Communication card for METASYS N2<br>Communication card for Modbus Plus<br>Communication card for Modbus TCP<br>Communication card for Modbus/Uni-Telway<br>Multi-pump card<br>Communication card for Profibus DP<br>Communication card for Profibus DP V1 |

## Complementary

|  |   |
|--|---|
| Product destination                        | Synchronous motors<br>Asynchronous motors   |
| Power supply voltage limits                | 323...528 V   |
| Power supply frequency                     | 50...60 Hz - 5...5 %  |
| Power supply frequency limits              | 47.5...63 Hz  |
| Continuous output current                  | 616 A at 2.5 kHz, 380 V - 3 phases<br>616 A at 2.5 kHz, 460 V - 3 phases  |
| Output frequency                           | 0.1...500 Hz  |
| Speed range                                | 1...100 in open-loop mode, without speed feedback   |
| Speed accuracy                             | +/- 10 % of nominal slip 0.2 Tn to Tn without speed feedback  |
| Torque accuracy                            | +/- 15 % in open-loop mode, without speed feedback  |
| Transient overtorque                       | 130 % of nominal motor torque +/- 10 % for 60 s   |
| Braking torque                             | <= 125 % with braking resistor<br>30 % without braking resistor   |
| Regulation loop                            | Frequency PI regulator  |
| Motor slip compensation                    | Not available in voltage/frequency ratio (2 or 5 points)<br>Can be suppressed<br>Automatic whatever the load<br>Adjustable  |
| Diagnostic                                 | 1 LED (red)drive voltage:   |
| Output voltage                             | <= power supply voltage   |
| Electrical isolation                       | Between power and control terminals   |
| Type of cable for mounting in an enclosure | With an IP21 or an IP31 kit: 3 wire(s)IEC cable at 40 °C, copper 70 °C / PVC<br>With UL Type 1 kit: 3 wire(s)UL 508 cable at 40 °C, copper 75 °C / PVC<br>Without mounting kit: 1 wire(s)IEC cable at 45 °C, copper 70 °C / PVC<br>Without mounting kit: 1 wire(s)IEC cable at 45 °C, copper 90 °C / XLPE/EPR |
| Electrical connection                      | Terminal 2.5 mm <sup>2</sup> / AWG 14 (AI1-/AI1+, AI2, AO1, R1A, R1B, R1C, R2A, R2B, LI1...LI6, PWR)<br>Terminal 4 x 185 mm <sup>2</sup> / 3 x 350 kcmil (L1/R, L2/S, L3/T, U/T1, V/T2, W/T3)<br>Terminal 4 x 185 mm <sup>2</sup> / 3 x 350 kcmil (PC/-, PO, PA/+)  |
| Tightening torque                          | 0.6 N.m (AI1-/AI1+, AI2, AO1, R1A, R1B, R1C, R2A, R2B, LI1...LI6, PWR)<br>41 N.m, 360 lb.in (PC/-, PO, PA/+)<br>41 N.m, 360 lb.in (L1/R, L2/S, L3/T, U/T1, V/T2, W/T3)  |
| Supply                                     | Internal supply for reference potentiometer (1 to 10 kOhm): 10.5 V DC, +/- 5 %, <10 mA with overload and short-circuit protection<br>Internal supply: 24 V DC (21...27 V), <200 mA with overload and short-circuit protection<br>External supply: 24 V DC (19...30 V)   |
| Analogue input number                      | 2   |
| Analogue input type                        | AI1-/AI1+ bipolar differential voltage: +/- 10 V DC 24 V max, resolution 11 bits + sign<br>AI2 software-configurable current: 0...20 mA, impedance: 242 Ohm, resolution 11 bits<br>AI2 software-configurable voltage: 0...10 V DC 24 V max, impedance: 30000 Ohm, resolution 11 bits                          |
| Sampling time                              | 2 ms +/- 0.5 ms (AI1-/AI1+) - analog input<br>2 ms +/- 0.5 ms (AI2) - analog input<br>2 ms +/- 0.5 ms (AO1) - analog output<br>2 ms +/- 0.5 ms (LI1...LI5) - discrete input   |

|                                     |   |
|-------------------------------------|---|
|                                     | 2 ms +/- 0.5 ms (LI6) if configured as logic input - discrete input   |
| Absolute accuracy precision         | +/- 0.6 % (AI1-/AI1+) for a temperature variation 60 °C<br>+/- 0.6 % (AI2) for a temperature variation 60 °C<br>+/- 1 % (AO1) for a temperature variation 60 °C   |
| Linearity error                     | +/- 0.15 % of maximum value (AI1-/AI1+)<br>+/- 0.15 % of maximum value (AI2)<br>+/- 0.2 % (AO1)   |
| Analogue output number              | 1   |
| Analogue output type                | AO1 software-configurable current, analogue output range 0...20 mA, impedance: 500 Ohm, resolution 10 bits<br>AO1 software-configurable voltage, analogue output range 0...10 V DC, impedance: 470 Ohm, resolution 10 bits<br>AO1 software-configurable logic output 10 V, 20 mA  |
| Discrete output number              | 2   |
| Discrete output type                | Configurable relay logic: (R1A, R1B, R1C) NO/NC - 100000 cycles<br>Configurable relay logic: (R2A, R2B) NO - 100000 cycles  |
| Maximum response time               | <= 100 ms in STO (Safe Torque Off)<br>R1A, R1B, R1C <= 7 ms, tolerance +/- 0.5 ms<br>R2A, R2B <= 7 ms, tolerance +/- 0.5 ms   |
| Minimum switching current           | 3 mA at 24 V DC for configurable relay logic  |
| Maximum switching current           | R1, R2: 2 A at 250 V AC inductive load, cos phi = 0.4 and L/R = 7 ms<br>R1, R2: 2 A at 30 V DC inductive load, cos phi = 0.4 and L/R = 7 ms<br>R1, R2: 5 A at 250 V AC resistive load, cos phi = 1 and L/R = 0 ms<br>R1, R2: 5 A at 30 V DC resistive load, cos phi = 1 and L/R = 0 ms  |
| Discrete input number               | 7   |
| Discrete input type                 | Programmable (LI1...LI5)24 V DC (<= 30 V), with level 1 PLC - 3500 Ohm<br>Switch-configurable (LI6)24 V DC (<= 30 V), with level 1 PLC - 3500 Ohm<br>Switch-configurable PTC probe (LI6)0...6 probes - 1500 Ohm<br>Safety input (PWR)24 V DC (<= 30 V) - 1500 Ohm   |
| Discrete input logic                | Negative logic (sink) (LI1...LI5), > 16 V (state 0), < 10 V (state 1)<br>Positive logic (source) (LI1...LI5), < 5 V (state 0), > 11 V (state 1)<br>Negative logic (sink) (LI6)if configured as logic input, > 16 V (state 0), < 10 V (state 1)<br>Positive logic (source) (LI6)if configured as logic input, < 5 V (state 0), > 11 V (state 1)  |
| Acceleration and deceleration ramps | S, U or customized<br>Automatic adaptation of ramp if braking capacity exceeded, by using resistor<br>Linear adjustable separately from 0.01 to 9000 s  |
| Braking to standstill               | By DC injection   |
| Protection type                     | Against exceeding limit speed: drive<br>Against input phase loss: drive<br>Break on the control circuit: drive<br>Input phase breaks: drive<br>Line supply overvoltage: drive<br>Line supply undervoltage: drive<br>Overcurrent between output phases and earth: drive<br>Overheating protection: drive<br>Overvoltages on the DC bus: drive<br>Power removal: drive<br>Short-circuit between motor phases: drive<br>Thermal protection: drive<br>Motor phase break: motor<br>Power removal: motor<br>Thermal protection: motor |
| Insulation resistance               | > 1 mOhm 500 V DC for 1 minute to earth   |
| Frequency resolution                | Analog input: 0.024/50 Hz<br>Display unit: 0.1 Hz   |
| Connector type                      | 1 RJ45 (on front face) for Modbus<br>1 RJ45 (on terminal) for Modbus<br>Male SUB-D 9 on RJ45 for CANopen  |
| Physical interface                  | 2-wire RS 485 for Modbus  |
| Transmission frame                  | RTU for Modbus  |
| Transmission rate                   | 4800 bps, 9600 bps, 19200 bps, 38.4 Kbps for Modbus on terminal<br>9600 bps, 19200 bps for Modbus on front face<br>20 kbps, 50 kbps, 125 kbps, 250 kbps, 500 kbps, 1 Mbps for CANopen   |
| Data format                         | 8 bits, 1 stop, even parity for Modbus on front face<br>8 bits, odd even or no configurable parity for Modbus on terminal   |
| Number of addresses                 | 1...127 for CANopen   |

|                    |                        |
|--------------------|------------------------|
| Method of access   | Slave CANopen          |
| Marking            | CE                     |
| Operating position | Vertical +/- 10 degree |
| Product weight     | 140 kg                 |
| Width              | 595 mm                 |
| Height             | 950 mm                 |
| Depth              | 377 mm                 |

## Environment

|                                       |  |
|---------------------------------------|--|
| Noise level                           | 68 dB conforming to 86/188/EEC   |
| Dielectric strength                   | 3535 V DC between earth and power terminals<br>5092 V DC between control and power terminals   |
| Electromagnetic compatibility         | Conducted radio-frequency immunity test level 3 conforming to IEC 61000-4-6<br>Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4<br>Electrostatic discharge immunity test level 3 conforming to IEC 61000-4-2<br>Radiated radio-frequency electromagnetic field immunity test level 3 conforming to IEC 61000-4-3<br>Voltage dips and interruptions immunity test conforming to IEC 61000-4-11   |
| Standards                             | EN 55011 class A group 2<br>EN/IEC 61800-3<br>EN 61800-3 environments 2 category C3<br>EN 61800-3 environments 1 category C3<br>EN/IEC 61800-5-1<br>UL Type 1<br>IEC 60721-3-3 class 3C2   |
| Product certifications                | DNV<br>NOM 117<br>GOST<br>C-Tick<br>CSA<br>UL  |
| Pollution degree                      | 3 conforming to EN/IEC 61800-5-1<br>3 conforming to UL 840   |
| Degree of protection                  | IP41 on upper part conforming to EN/IEC 60529<br>IP41 on upper part conforming to EN/IEC 61800-5-1<br>IP54 on lower part conforming to EN/IEC 60529<br>IP54 on lower part conforming to EN/IEC 61800-5-1<br>IP00 conforming to EN/IEC 60529<br>IP00 conforming to EN/IEC 61800-5-1<br>IP30 on side parts conforming to EN/IEC 60529<br>IP30 on side parts conforming to EN/IEC 61800-5-1<br>IP30 on the front panel conforming to EN/IEC 60529<br>IP30 on the front panel conforming to EN/IEC 61800-5-1 |
| Vibration resistance                  | 0.6 gn (f= 10...200 Hz) conforming to EN/IEC 60068-2-6<br>1.5 mm peak to peak (f= 3...10 Hz) conforming to EN/IEC 60068-2-6  |
| Shock resistance                      | 4 gn for 11 ms conforming to EN/IEC 60068-2-27   |
| Relative humidity                     | 5...95 % without condensation conforming to IEC 60068-2-3<br>5...95 % without dripping water conforming to IEC 60068-2-3   |
| Ambient air temperature for operation | -10...45 °C (without)<br>45...60 °C (with derating factor)   |
| Ambient air temperature for storage   | -25...70 °C  |
| Operating altitude                    | <= 1000 m without<br>1000...3000 m with current derating 1 % per 100 m   |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a>  |

|                          |   |
|--------------------------|---|
| Environmental Disclosure | Product Environmental Profile   |
| Circularity Profile      | No need of specific recycling operations  |
| WEEE                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

#### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|