Product data sheet Characteristics

METSEDM6000

DM6000 digital meter with basic readings - no communication





Main

Range of product	PowerLogic	v v
Device short name	DM6000	<u>8</u>
Product or component type	Multimeter	9

Complementary

Device application	Preventive maintenance	-
	Equipment monitoring	
	Power monitoring	
Type of measurement	Current	
	Voltage	
	Frequency	
	Power factor	;
	Phase unbalance	
	Phase angle	•
	RPM	
[Us] rated supply voltage	44277 V AC 50/60 Hz	
	44277 V DC	:
Network frequency	4565 Hz	:
Maximum power consumption in VA	3 VA at 240 V AC	
Display type	LED indicator	
Sampling rate	20 samples/cycle	
Measurement current	1 A	
	5 A	
Analogue input type	Current 0.056 A (impedance <= 0.1 Ohm)	
Measurement voltage	80480 V AC phase to phase	
Measurement accuracy	Frequency 0.1 %	
	Power factor 1 %	
	Voltage 1 % 46277 V	
	Current 1 % 0.056 A	

Environment

Electromagnetic compatibility	Electrostatic discharge immunity test: , conforming to IEC 61000-4-2 Susceptibility to electromagnetic fields: , conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test: , conforming to IEC 61000-4-4 1.2/50 µs shock waves immunity test: , conforming to IEC 61000-4-5 Conducted RF disturbances: , conforming to IEC 61000-4-6 Immunity to impulse waves: , conforming to IEC 61000-4-12 Conducted and radiated emissions: , A, conforming to CISPR 11 Immunity to microbreaks and voltage drops: , conforming to IEC 61000-4-11
Mounting mode	Flush-mounted
Type of installation	Indoor installation
Overvoltage category	III
IP degree of protection	IP40 back: IP51 front face:
Pollution degree	2
Ambient air temperature for operation	-1060 °C
Ambient air temperature for storage	-2570 °C
Relative humidity	95 %
Operating altitude	02000 m
Standards	IEC 61010 UL 508
Product certifications	CE
Width	96 mm
Depth	80 mm
Height	96 mm
Net weight	0.4 kg

Offer Sustainability

onor odotamasmity		
Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Contractual warranty

Warranty	18 months	