# Product data sheet Characteristics

# TMC2AQ2C





#### Main

Range of product	Modicon M221
Product or component type	Analogue output cartridge
Product compatibility	Modicon M221C

## Complementary

Analogue output number	2	
Analogue output type	Current: 420 mA	
Analogue output resolution	12 bits	
LSB value	3.91 µA 420 mA current	
Load type	Resistive	
Load impedance ohmic	<= 500 Ohm	
Conversion time	20 ms	
Stabilisation time	40 Ms	
Absolute accuracy error	+/- 1 % of full scale +/- 0.3 % of full scale at 25 °C	
Temperature drift	+/- 0.02 %FS/°C	
Repeat accuracy	+/- 0.4 %FS	
Non-linearity	+/- 0.01 %FS	
Cross talk	<= 1 LSB	
Type of cable	Twisted shielded pairs cable	
Electrical connection	3 x 1.5 mm² 2 screw terminal blocks with pitch 3.81 mm adjustment for outputs	
Maximum cable distance between devices	Twisted shielded pairs cable: <30 m for output	
Insulation	Non-insulated between analogue output and internal logic	
Height	41 Mm	
Depth	15 Mm	
Width	35 Mm	
Net weight	0.015 Kg	

### **Environment**

Livioninent				
Immunity to microbreaks	10 Ms			

# Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☐ End Of Life Information	

Product Life Status:	Commercialised	