Product data sheet Characteristics

TSXRKY6C

non-extendable rack - for single rack configuration - 6 slots - IP20



Commercial status

Discontinued on: 31 December 2017

To be end-of-service on: 31 December 2025

Main

Range of product

Product or component type	Non-extendable rack	•
Product specific application	For single rack configuration	
Complementary		
Number of slots	6	
Product compatibility	TSXP57 processor	
	TSXPSY power supply	
	Specific application module	

	Specific application module I/O module
Fixing mode	By 4 M6 screws (panel) By clips (35 mm symmetrical DIN rail)
Marking	CE

1.47 kg

Modicon Premium Automation platform

Environment

Net weight

Standards	CSA C22.2 No 142	of pesulon sed for
	IEC 61131-2	es es
	89/336/EEC	- -
	CSA C22.2 No 213 Class I Division 2 Group B	not to be
	CSA C22.2 No 213 Class I Division 2 Group C	2
	UL 508	<u></u>
	93/68/EEC	
	CSA C22.2 No 213 Class I Division 2 Group A	substitute for and is
	73/23/EEC	i di
	CSA C22.2 No 213 Class I Division 2 Group D	sqn
	92/31/EEC	a
Product certifications	BV	
	LR	e
	ABS	<u>.</u>
	GL	0
	RINA	
	RMRS	tatic
	DNV	e B
Ambient air temperature for operation	060 °C	This documentation is not intended as
Ambient air temperature for storage	-2570 °C	
Relative humidity	1095 % without condensation for operation	
		C)

5...95 % without condensation for storage

Operating altitude	02000 m
Protective treatment	TC Conformal coating Humiseal 1A33
IP degree of protection	IP20
Pollution degree	2

Packing Units

Package 1 Weight	1.286 kg
Package 1 Height	52.000 mm
Package 1 width	205.000 mm
Package 1 Length	350.000 mm

Contractual warranty

Warranty	18 months

TSXRKY6C is replaced by:

Harsh environment BMXXBP0800H

ruggedized rack M340 - 8 slots - panel, plate or DIN rail mounting

Qty 1

Reason for Substitution: End of life | Substitution date: 31 December 2017

