## Product data sheet Characteristics

# TSXRKY8C

non-extendable rack - for single rack configuration - 8 slots - IP20



## Commercial status

Discontinued on: 31 December 2017

To be end-of-service on: 31 December 2025

#### Main

Range of product	Modicon Premium Automation platform	
Product or component type	Non-extendable rack	
Product specific application	For single rack configuration	9
		C C

#### Complementary

Complementary		
Number of slots	8	
Product compatibility	I/O module TSXP57 processor Specific application module TSXPSY power supply	
Fixing mode	By 4 M6 screws (panel) By clips (35 mm symmetrical DIN rail)	
Marking	CE	
Net weight	1.76 kg	

#### Environment

Standards	UL 508	— j
Standards		used for
	93/68/EEC	Sn 6
	73/23/EEC	not to be
	CSA C22.2 No 142	t t
	CSA C22.2 No 213 Class I Division 2 Group C	S
	IEC 61131-2	<u>5</u>
	CSA C22.2 No 213 Class I Division 2 Group A	Z.
	CSA C22.2 No 213 Class I Division 2 Group B	te fe
	89/336/EEC	ŧ
	92/31/EEC	substitute for and is
	CSA C22.2 No 213 Class I Division 2 Group D	σ
Product certifications	RINA	not intended as
	BV	end
	RMRS	ij
	DNV	2
	LR	.82
	GL	atio
	ABS	meni
Ambient air temperature for operation	060 °C	This documentation is
Ambient air temperature for storage	-2570 °C	This
Relative humidity	1095 % without condensation for operation	claimer:

#### 5...95 % without condensation for storage

Operating altitude	02000 m
Protective treatment	Conformal coating Humiseal 1A33 TC
IP degree of protection	IP20
Pollution degree	2

## **Packing Units**

Package 1 Weight	1.623 kg	
Package 1 Height	55.000 mm	
Package 1 width	205.000 mm	
Package 1 Length	420.000 mm	

## Contractual warranty

Warranty	18 months

## TSXRKY8C is replaced by:

## Standard environment BMXXBP0800

rack M340 - 8 slots - panel, plate or DIN rail mounting

Qty 1

Reason for Substitution: End of life | Substitution date: 31 December 2017

