

# Product datasheet

Specifications



## Acti9 iID K - residual current circuit breaker - 4P - 40A - 300mA - type AC

A9R75440

! Discontinued on: 01 March 2022

! Discontinued

A9R75440 has not been replaced. Please contact your customer care centre for more information.

### Main

Range	Acti 9
Product name	Acti9 iID K
Product or component type	Residual current circuit breaker (RCCB)
Device short name	iID K
Poles description	4P
Neutral position	Left
[In] rated current	40 A
Network type	AC
Earth-leakage sensitivity	300 mA
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Type AC
Quality labels	VDE

### Complementary

Device location in system	Outgoer
Network frequency	50/60 Hz
[Ue] rated operational voltage	380...415 V AC 50/60 Hz
Residual current tripping technology	Voltage independent
Rated breaking and making capacity	Idm 500 A Im 500 A
Rated conditional short-circuit current	GL63: Inc 4.5 kA K60: Inc 6 kA C60: Inc 6 kA
[Ui] rated insulation voltage	440 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	4 kV
Surge current	250 A
Contact position indicator	No
Control type	Toggle

<b>Mounting mode</b>	Clip-on
<b>Mounting support</b>	DIN rail
<b>9 mm pitches</b>	8
<b>Height</b>	85 mm
<b>Width</b>	72 mm
<b>Depth</b>	69 mm
<b>Net weight</b>	0.37 kg
<b>Colour</b>	White
<b>Mechanical durability</b>	5000 cycles
<b>Electrical durability</b>	AC-1: 2000 cycles
<b>Locking options description</b>	Padlocking device
<b>Connections - terminals</b>	Tunnel type terminals top or bottom 1...35 mm <sup>2</sup> rigid Tunnel type terminals top or bottom 1...25 mm <sup>2</sup> flexible Tunnel type terminals top or bottom 1...25 mm <sup>2</sup> flexible with ferrule
<b>Wire stripping length</b>	16 mm for top or bottom connection
<b>Tightening torque</b>	3.5 N.m top or bottom

## Environment

<b>Standards</b>	EN/IEC 61008-1
<b>IP degree of protection</b>	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
<b>Pollution degree</b>	2
<b>Electromagnetic compatibility</b>	8/20 µs impulse withstand, 200 A conforming to EN/IEC 61008-1
<b>Ambient air temperature for operation</b>	-5...60 °C
<b>Ambient air temperature for storage</b>	-40...85 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Weight</b>	360.6 g
<b>Package 1 Height</b>	7.5 cm
<b>Package 1 width</b>	8 cm
<b>Package 1 Length</b>	10 cm
<b>Unit Type of Package 2</b>	S03
<b>Number of Units in Package 2</b>	27
<b>Package 2 Weight</b>	11.08 kg
<b>Package 2 Height</b>	30 cm
<b>Package 2 width</b>	30 cm
<b>Package 2 Length</b>	40 cm
<b>Unit Type of Package 3</b>	BB1
<b>Number of Units in Package 3</b>	3
<b>Package 3 Weight</b>	1.147 kg
<b>Package 3 Height</b>	9 cm
<b>Package 3 width</b>	10.7 cm

---

Package 3 Length	25.5 cm
------------------	---------

---

## Offer Sustainability

---

Sustainable offer status	Green Premium product
--------------------------	-----------------------

---

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

---

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
-------------------	--

---

Mercury free	Yes
--------------	-----

---

RoHS exemption information	<a href="#">Yes</a>
----------------------------	---------------------

---

China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
-----------------------	---

---

Environmental Disclosure	<a href="#">Product Environmental Profile</a>
--------------------------	---

---

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------	---

---

Halogen content performance	Halogen free plastic parts product
-----------------------------	------------------------------------

---

## Contractual warranty

---

Warranty	18 months
----------	-----------

---