

product type designation



Figure similar

CP 443-1

SIPLUS NET CP 443-1 based on 6GK7443-1EX30-0XE0 with conformal coating, 0...+60 °C, 2x 10/100 Mbps (IE switch); RJ 45 ports; ISO; TCP; UDP; PROFINET IO controller S7 communication; open communication (send/ receive); S7 routing; IP configuration via DHCP/block; IP access control list; time- -of-day synchronization; extended Web diagnostics; fast start up; support for PROFINergy

transfer rate

transfer rate	
• at the 1st interface	10 ... 100 Mbit/s

interfaces

number of interfaces / according to Industrial Ethernet	2
number of electrical connections	
• at the 1st interface / according to Industrial Ethernet	2
type of electrical connection	
• at the 1st interface / according to Industrial Ethernet	RJ45 port
design of the removable storage	
• C-PLUG	No

supply voltage, current consumption, power loss

type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	5 V
relative symmetrical tolerance / at DC	
• at 5 V	5 %
consumed current	
• from backplane bus / at DC / at 5 V / typical	1.4 A
power loss [W]	8.6 W

ambient conditions

ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
installation altitude / at height above sea level / maximum	5000 m
ambient condition / relating to ambient temperature - air pressure - installation altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
relative humidity	
• with condensation / according to IEC 60068-2-38 / maximum	100 %; RH including condensation/frost (no commissioning when condensation is present), horizontal installation
chemical resistance / to commercially available cooling lubricants	Yes; incl. airborne diesel and oil droplets
resistance to biologically active substances	
• conformity according to EN 60721-3-3	Yes; Class 3B2 mold and fungal spores (excluding fauna), Class 3B3 on request
• conformity according to EN 60721-3-6	Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)
resistance to chemically active substances	
• conformity according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray in accordance with EN 60068-2-52 (Severity 3). The supplied plug covers must remain in place on the unused

<ul style="list-style-type: none"> conformity according to EN 60721-3-6 	interfaces during operation. Yes
resistance to mechanically active substances <ul style="list-style-type: none"> conformity according to EN 60721-3-3 conformity according to EN 60721-3-6 	Yes; Class 3S4 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation. Yes; Class 6S3 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
coating / for equipped printed circuit board / according to EN 61086	Yes; Class 2 for high availability
type of coating / protection against pollution according to EN 60664-3	Yes; Protection of the type 1
type of test / of the coating / according to MIL-I-46058C	Yes; Coating discoloration during service life possible
product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, class A
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-400 single width
width	25 mm
height	290 mm
depth	210 mm
net weight	0.7 kg
product features, product functions, product components / general	
number of units <ul style="list-style-type: none"> per CPU / maximum note 	14 max. 4 as PN IO ctrl.
performance data / open communication	
number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	64
data volume <ul style="list-style-type: none"> as user data per ISO connection / for open communication / by means of SEND/RECEIVE blocks / maximum as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum 	8 Kibyte 8 Kibyte 8 Kibyte 2 Kibyte
number of possible connections / for open communication <ul style="list-style-type: none"> by means of T blocks / maximum 	64
data volume <ul style="list-style-type: none"> as user data per ISO on TCP connection / for open communication / by means of T blocks / maximum 	1452 byte
performance data / S7 communication	
number of possible connections / for S7 communication <ul style="list-style-type: none"> maximum with PG connections / maximum 	128; when using several CPUs 2
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	128
performance data / PROFINET communication / as PN IO controller	
product function / PROFINET IO controller	Yes
number of PN IO devices / on PROFINET IO controller / operable / total	128
number of PN IO IRT devices / on PROFINET IO controller / operable	64
number of external PN IO lines / with PROFINET / per rack	4
data volume <ul style="list-style-type: none"> as user data for input variables / as PROFINET IO controller / maximum as user data for output variables / as PROFINET IO controller / maximum as user data for input variables per PN IO device / as PROFINET IO controller / maximum 	4 Kibyte 4 Kibyte 1433 byte

<ul style="list-style-type: none"> • as user data for output variables per PN IO device / as PROFINET IO controller / maximum 	1433 byte
<ul style="list-style-type: none"> • as user data for input variables per PN IO device / for each sub-module as PROFINET IO controller / maximum 	240 byte
<ul style="list-style-type: none"> • as user data for output variables per PN IO device / for each sub-module as PROFINET IO controller / maximum 	240 byte
performance data / telecontrol	
protocol / is supported	
<ul style="list-style-type: none"> • TCP/IP 	Yes
product functions / management, configuration, engineering	
product function / MIB support	Yes
protocol / is supported	
<ul style="list-style-type: none"> • SNMP v1 	Yes
<ul style="list-style-type: none"> • DCP 	Yes
<ul style="list-style-type: none"> • LLDP 	Yes
configuration software	
<ul style="list-style-type: none"> • required 	STEP 7 V5.5 SP3 or higher / STEP 7 Professional V12 (TIA Portal) or higher
product functions / diagnostics	
product function / web-based diagnostics	Yes
product functions / switch	
product feature / switch	Yes
product function	
<ul style="list-style-type: none"> • switch-managed 	No
<ul style="list-style-type: none"> • with IRT / PROFINET IO switch 	Yes
<ul style="list-style-type: none"> • configuration with STEP 7 	Yes
product functions / redundancy	
product function	
<ul style="list-style-type: none"> • ring redundancy 	Yes
<ul style="list-style-type: none"> • redundancy manager 	Yes
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
standards, specifications, approvals	
reference code	
<ul style="list-style-type: none"> • according to IEC 81346-2:2019 	KEC
further information / internet links	
internet link	
<ul style="list-style-type: none"> • to website: Selection guide for cables and connectors 	https://support.industry.siemens.com/cs/ww/en/view/109766358
<ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool 	https://www.siemens.com/tstcloud
<ul style="list-style-type: none"> • to website: Industrial communication 	https://www.siemens.com/simatic-net
<ul style="list-style-type: none"> • to web page: SiePortal 	https://sieportal.siemens.com/
<ul style="list-style-type: none"> • to website: Image database 	https://www.automation.siemens.com/bilddb
<ul style="list-style-type: none"> • to website: CAX-Download-Manager 	https://siemens.com/cax
<ul style="list-style-type: none"> • to website: Industry Online Support 	https://support.industry.siemens.com
security information	
security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)</p>
Approvals / Certificates	
General Product Approval	EMV

[Miscellaneous](#)



[Manufacturer Declaration](#)



[KC](#)



For use in hazardous locations

[CCC-Ex](#)



last modified:

2/28/2025 