

SIMATIC S7-400, interface module Send IM 460-0 for central coupling without PS transfer, with C-bus

Input current	
from backplane bus 5 V DC, max.	140 mA
Power loss	
Power loss, max.	700 mW
Hardware configuration	
Cable length between first and last interface module, max.	5 m
connection method	
termination plug	6ES7461-0AA0-7AA0
Dimensions	
Width	25 mm
Height	290 mm
Depth	280 mm
Weights	
Weight, approx.	600 g
Classifications	

	Version	Classification
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates
General Product Approval

Miscellaneous



KC



EMV	For use in hazardous locations				
				EM	
For use in hazardous locations			Marine / Shipping		



IECEEx

[Type Examination Certificate](#)



ATEX



ABS



DNV

Marine / Shipping



LRS

[NK / Nippon Kaiji Kyokai](#)



PRS



RINA



RMRS

[CCS \(China Classification Society\)](#)

last modified:

3/12/2024