



SIMATIC S7-400, interface module receiver IM 461-1 for central coupling with PS transfer, without C bus,

Input current	
from backplane bus 5 V DC, max.	120 mA
Power loss	
Power loss, max.	600 mW
Hardware configuration	
Cable length between first and last interface module, max.	1.5 m
Dimensions	
Width	25 mm
Height	290 mm
Depth	280 mm
Weights	
Weight, approx.	610 g
Classifications	

	Version	Classification
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates	
General Product Approval	



Miscellaneous



KC



EMV	For use in hazardous locations
-----	--------------------------------



RCM



RCM



IECEX



ATEX

[FM](#)



CCC

For use in hazardous locations

Marine / Shipping



IECEX

[Type Examination Certificate](#)



ATEX



ABS



DNV

Marine / Shipping



LRS

[NK / Nippon Kaiji Kyokai](#)



PRS



RINA



RMRS

[CCS \(China Classification Society\)](#)

last modified:

3/12/2024