

**Siemens
EcoTech**



SIMATIC S7-1500 analog input module AI 8xU/I/RTD/TC ST, 16 bit resolution, accuracy 0.3%, 8 channels in groups of 8; 4 channels for RTD measurement, common mode voltage 10 V; Diagnostics; Hardware interrupts; Delivery including infed element, shield bracket and shield terminal: Front connector (screw terminals or push-in) to be ordered separately

General information

Product type designation	AI 8xU/I/RTD/TC ST
HW functional status	FS04
Firmware version	V2.0.0
• FW update possible	Yes

Product function

• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	No
• Prioritized startup	No
• Measuring range scalable	No
• Scalable measured values	No
• Adjustment of measuring range	No

Engineering with

• STEP 7 TIA Portal configurable/integrated from version	V12 / V12
• STEP 7 configurable/integrated from version	V5.5 SP3 / -
• PROFIBUS from GSD version/GSD revision	V1.0 / V5.1
• PROFINET from GSD version/GSD revision	V2.3 / -

Operating mode

• Oversampling	No
• MSI	Yes

CiR - Configuration in RUN

Reparameterization possible in RUN	Yes
Calibration possible in RUN	Yes

Supply voltage

Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes

Input current

Current consumption, max.	255 mA; with 19.2 V supply
---------------------------	----------------------------

Encoder supply

24 V encoder supply	
• Short-circuit protection	Yes
• Output current, max.	20 mA; Max. 47 mA per channel for a duration < 10 s

Power

Power consumption from the backplane bus	0.7 W
--	-------

Power loss

Power loss, typ.	2.7 W
Analog inputs	
Number of analog inputs	8
• For current measurement	8
• For voltage measurement	8
• For resistance/resistance thermometer measurement	4
• For thermocouple measurement	8
permissible input voltage for voltage input (destruction limit), max.	28.8 V
permissible input current for current input (destruction limit), max.	40 mA
Constant measurement current for resistance-type transmitter, typ.	150 Ohm, 300 Ohm, 600 Ohm, Pt100, Pt200, Ni100: 1.25 mA; 6 000 Ohm, Pt500, Pt1000, Ni1000, LG-Ni1000: 0.625 mA; PTC: 0.472 mA
Technical unit for temperature measurement adjustable	Yes; °C/°F/K
Input ranges (rated values), voltages	
• 0 to +5 V	No
• 0 to +10 V	No
• 1 V to 5 V	Yes
— Input resistance (1 V to 5 V)	100 kΩ
• -1 V to +1 V	Yes
— Input resistance (-1 V to +1 V)	10 MΩ
• -10 V to +10 V	Yes
— Input resistance (-10 V to +10 V)	100 kΩ
• -2.5 V to +2.5 V	Yes
— Input resistance (-2.5 V to +2.5 V)	10 MΩ
• -25 mV to +25 mV	No
• -250 mV to +250 mV	Yes
— Input resistance (-250 mV to +250 mV)	10 MΩ
• -5 V to +5 V	Yes
— Input resistance (-5 V to +5 V)	100 kΩ
• -50 mV to +50 mV	Yes
— Input resistance (-50 mV to +50 mV)	10 MΩ
• -500 mV to +500 mV	Yes
— Input resistance (-500 mV to +500 mV)	10 MΩ
• -80 mV to +80 mV	Yes
— Input resistance (-80 mV to +80 mV)	10 MΩ
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
— Input resistance (0 to 20 mA)	25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC
• -20 mA to +20 mA	Yes
— Input resistance (-20 mA to +20 mA)	25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC
• 4 mA to 20 mA	Yes
— Input resistance (4 mA to 20 mA)	25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC
Input ranges (rated values), thermocouples	
• Type B	Yes
— Input resistance (Type B)	10 MΩ
• Type C	No
• Type E	Yes
— Input resistance (Type E)	10 MΩ
• Type J	Yes
— Input resistance (type J)	10 MΩ
• Type K	Yes
— Input resistance (Type K)	10 MΩ
• Type L	No
• Type N	Yes
— Input resistance (Type N)	10 MΩ
• Type R	Yes
— Input resistance (Type R)	10 MΩ
• Type S	Yes
— Input resistance (Type S)	10 MΩ
• Type T	Yes
— Input resistance (Type T)	10 MΩ

• Type TXK/TXK(L) to GOST	No
Input ranges (rated values), resistance thermometer	
• Cu 10	No
• Cu 10 according to GOST	No
• Cu 50	No
• Cu 50 according to GOST	No
• Cu 100	No
• Cu 100 according to GOST	No
• Ni 10	No
• Ni 10 according to GOST	No
• Ni 100	Yes; Standard/climate
— Input resistance (Ni 100)	10 MΩ
• Ni 100 according to GOST	No
• Ni 1000	Yes; Standard/climate
— Input resistance (Ni 1000)	10 MΩ
• Ni 1000 according to GOST	No
• LG-Ni 1000	Yes; Standard/climate
— Input resistance (LG-Ni 1000)	10 MΩ
• Ni 120	No
• Ni 120 according to GOST	No
• Ni 200 according to GOST	No
• Ni 500	No
• Ni 500 according to GOST	No
• Pt 10	No
• Pt 10 according to GOST	No
• Pt 50	No
• Pt 50 according to GOST	No
• Pt 100	Yes; Standard/climate
— Input resistance (Pt 100)	10 MΩ
• Pt 100 according to GOST	No
• Pt 1000	Yes; Standard/climate
— Input resistance (Pt 1000)	10 MΩ
• Pt 1000 according to GOST	No
• Pt 200	Yes; Standard/climate
— Input resistance (Pt 200)	10 MΩ
• Pt 200 according to GOST	No
• Pt 500	Yes; Standard/climate
— Input resistance (Pt 500)	10 MΩ
• Pt 500 according to GOST	No
Input ranges (rated values), resistors	
• 0 to 150 ohms	Yes
— Input resistance (0 to 150 ohms)	10 MΩ
• 0 to 300 ohms	Yes
— Input resistance (0 to 300 ohms)	10 MΩ
• 0 to 600 ohms	Yes
— Input resistance (0 to 600 ohms)	10 MΩ
• 0 to 3000 ohms	No
• 0 to 6000 ohms	Yes
— Input resistance (0 to 6000 ohms)	10 MΩ
• PTC	Yes
— Input resistance (PTC)	10 MΩ
Thermocouple (TC)	
Temperature compensation	
— parameterizable	Yes
— internal temperature compensation	Yes
— external temperature compensation via RTD	Yes
— Compensation for 0 °C reference point temperature	Yes; fixed value can be set
— Reference channel of the module	Yes
Cable length	
• shielded, max.	800 m; for U/I, 200 m for R/RTD, 50 m for TC
Analog value generation for the inputs	

Integration and conversion time/resolution per channel	
- Resolution with overrange (bit including sign), max. - Integration time, parameterizable - Integration time (ms) - Basic conversion time, including integration time (ms) — additional conversion time for wire-break monitoring — additional conversion time for resistance measurement - Interference voltage suppression for interference frequency f1 in Hz - Time for offset calibration (per module)	16 bit Yes 2,5 / 16,67 / 20 / 100 ms 9 / 23 / 27 / 107 ms 9 ms (to be considered in R/RTD/TC measurement) 150 ohm, 300 ohm, 600 ohm, Pt100, Pt200, Ni100: 2 ms, 6000 ohm, Pt500, Pt1000, Ni1000, LG-Ni1000, PTC: 4 ms 400 / 60 / 50 / 10 Hz Basic conversion time of the slowest channel
Smoothering of measured values	
- parameterizable - Step: None - Step: low - Step: Medium - Step: High	Yes Yes Yes Yes Yes
Encoder	
Connection of signal encoders	
- for voltage measurement - for current measurement as 2-wire transducer — Burden of 2-wire transmitter, max. - for current measurement as 4-wire transducer - for resistance measurement with two-wire connection - for resistance measurement with three-wire connection - for resistance measurement with four-wire connection	Yes Yes 820 Ω Yes Yes; Only for PTC Yes; All measuring ranges except PTC; internal compensation of the cable resistances Yes; All measuring ranges except PTC
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.02 %
Temperature error (relative to input range), (+/-)	0.005 %/K; With TC type T 0.02 $\pm$ % / K
Crosstalk between the inputs, max.	-80 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.02 %
Temperature error of internal compensation	± 6 °C
Operational error limit in overall temperature range	
- Voltage, relative to input range, (+/-) - Current, relative to input range, (+/-) - Resistance, relative to input range, (+/-) - Resistance thermometer, relative to input range, (+/-) - Thermocouple, relative to input range, (+/-)	0.3 % 0.3 % 0.3 % Ptxxx standard: ± 1.5 K, Ptxxx climate: ± 0.5 K, Nixxx standard: ± 0.5 K, Nixxx climate: ± 0.3 K Type B: > 600 °C ± 4.6 K, type E: > -200 °C ± 1.5 K, type J: > -210 °C ± 1.9 K, type K: > -200 °C ± 2.4 K, type N: > -200 °C ± 2.9 K, type R: > 0 °C ± 4.7 K, type S: > 0 °C ± 4.6 K, type T: > -200 °C ± 2.4 K
Basic error limit (operational limit at 25 °C)	
- Voltage, relative to input range, (+/-) - Current, relative to input range, (+/-) - Resistance, relative to input range, (+/-) - Resistance thermometer, relative to input range, (+/-) - Thermocouple, relative to input range, (+/-)	0.1 % 0.1 % 0.1 % Ptxxx standard: ± 0.7 K, Ptxxx climate: ± 0.2 K, Nixxx standard: ± 0.3 K, Nixxx climate: ± 0.15 K Type B: > 600 °C ± 1.7 K, type E: > -200 °C ± 0.7 K, type J: > -210 °C ± 0.8 K, type K: > -200 °C ± 1.2 K, type N: > -200 °C ± 1.2 K, type R: > 0 °C ± 1.9 K, type S: > 0 °C ± 1.9 K, type T: > -200 °C ± 0.8 K
Interference voltage suppression for $f = n \times (f1 \pm 1 \%)$, f1 = interference frequency	
- Series mode interference (peak value of interference < rated value of input range), min. - Common mode voltage, max. - Common mode interference, min.	40 dB 10 V 60 dB
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
- Diagnostic alarm - Limit value alarm	Yes Yes; two upper and two lower limit values in each case
Diagnoses	
Monitoring the supply voltage	Yes

• Wire-break • Overflow/underflow	Yes; Only for 1 to 5 V, 4 to 20 mA, TC, R, and RTD Yes		
Diagnostics indication LED			
• RUN LED • ERROR LED • Monitoring of the supply voltage (PWR-LED) • Channel status display • for channel diagnostics • for module diagnostics	Yes; green LED Yes; red LED Yes; green LED Yes; green LED Yes; red LED Yes; red LED		
Potential separation			
Potential separation channels			
• between the channels • between the channels, in groups of • between the channels and backplane bus • between the channels and the power supply of the electronics	No 8 Yes Yes		
Permissible potential difference			
between the inputs (UCM)	20 V DC		
Between the inputs and MANA (UCM)	10 V DC		
Isolation			
Isolation tested with	707 V DC (type test)		
Standards, approvals, certificates			
Siemens Eco Profile (SEP)	Siemens EcoTech		
Suitable for applications according to AMS 2750	Yes; Declaration of Conformity, see online support entry 109757262		
Suitable for applications according to CQI-9	Yes; Based on AMS 2750 E		
Ecological footprint			
• environmental product declaration	Yes		
Global warming potential			
— global warming potential, (total) [CO2 eq]	38.6 kg		
— global warming potential, (during production) [CO2 eq]	14.4 kg		
— global warming potential, (during operation) [CO2 eq]	24.6 kg		
— global warming potential, (after end of life cycle) [CO2 eq]	-0.44 kg		
product functions / security / header			
signed firmware update	No		
data integrity	No		
Ambient conditions			
Ambient temperature during operation			
• horizontal installation, min. • horizontal installation, max. • vertical installation, min. • vertical installation, max.	-25 °C; From FS08 60 °C -25 °C; From FS08 40 °C		
Altitude during operation relating to sea level			
• Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual		
Dimensions			
Width	35 mm		
Height	147 mm		
Depth	129 mm		
Weights			
Weight, approx.	310 g		
Other			
Note:	Additional basic error and noise for integration time = 2.5 ms: Voltage: ±250 mV (±0.02%), ±80 mV (±0.05%), ±50 mV (±0.05%); resistance: 150 ohms ±0.02%; resistance thermometer: Pt100 climate: ±0.08 K, Ni100 climate: ±0.08 K; thermocouple: Type B, R, S: ±3 K, type E, J, K, N, T: ±1 K		
Classifications			
		Version	Classification
	eClass	14	27-24-22-01
	eClass	12	27-24-22-01

eClass	9.1	27-24-22-01
eClass	9	27-24-22-01
eClass	8	27-24-22-01
eClass	7.1	27-24-22-01
eClass	6	27-24-22-01
ETIM	9	EC001420
ETIM	8	EC001420
ETIM	7	EC001420
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

[Manufacturer Declaration](#)



[Declaration of Conformity](#)
[Miscellaneous](#)


General Product Approval

For use in hazardous locations

[Metrological Approval](#)
[KC](#)



[FM](#)


For use in hazardous locations

[FM](#)
[CCC-Ex](#)


[Type Examination Certificate](#)


[Miscellaneous](#)

Marine / Shipping






[NK / Nippon Kaiji Kyokai](#)


Marine / Shipping

Environment


[CCS \(China Classification Society\)](#)





last modified:

4/7/2025 