



SIMATIC S7-1500, analog output module AQ 4xU/I HF, 16-bit resolution accuracy 0.1%, 4 channels in groups of 1, common mode voltage: 30 V AC/60 V DC, diagnostics; substitute value, isochronous mode; the module supports the safety-oriented shutdown of load groups up to SIL2 according to EN IEC 62061:2021 and Category 3 / PL d according to EN ISO 13849-1:2015. delivery including infeed element, shielding bracket and shield terminal: front connector (screw terminals or push-in) to be ordered separately

| General information | |
|--|---|
| Product type designation | AQ 4xU/I HF |
| HW functional status | from FS01 |
| Firmware version | V1.1.0 |
| • FW update possible | Yes |
| Product function | |
| • I&M data | Yes; I&M0 to I&M3 |
| • Isochronous mode | Yes |
| • Prioritized startup | Yes |
| Engineering with | |
| • STEP 7 TIA Portal configurable/integrated from version | V14 / - |
| • STEP 7 configurable/integrated from version | V5.5 SP3 / - |
| • PROFIBUS from GSD version/GSD revision | V1.0 / V5.1 |
| • PROFINET from GSD version/GSD revision | V2.3 / - |
| Operating mode | |
| • Oversampling | No |
| • MSO | Yes |
| CiR - Configuration in RUN | |
| Reparameterization possible in RUN | Yes |
| Calibration possible in RUN | Yes |
| Supply voltage | |
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 19.2 V |
| permissible range, upper limit (DC) | 28.8 V |
| Reverse polarity protection | Yes |
| Input current | |
| Current consumption, max. | 160 mA |
| Power | |
| Power consumption from the backplane bus | 0.95 W |
| Power loss | |
| Power loss, typ. | 5 W |
| Analog outputs | |
| Number of analog outputs | 4 |
| Voltage output, short-circuit protection | Yes |
| Voltage output, short-circuit current, max. | 24 mA |
| Current output, no-load voltage, max. | 22 V |
| Cycle time (all channels), min. | 125 µs; independent of number of activated channels |
| Output ranges, voltage | |
| • 0 to 10 V | Yes |
| • 1 V to 5 V | Yes |

| | |
|--|---|
| • -5 V to +5 V | No |
| • -10 V to +10 V | Yes |
| Output ranges, current | |
| • 0 to 20 mA | Yes |
| • -20 mA to +20 mA | Yes |
| • 4 mA to 20 mA | Yes |
| Connection of actuators | |
| • for voltage output two-wire connection | Yes |
| • for voltage output four-wire connection | Yes |
| • for current output two-wire connection | Yes |
| Load impedance (in rated range of output) | |
| • with voltage outputs, min. | 1 kΩ; 0.5 kΩm at 1 to 5 V |
| • with voltage outputs, capacitive load, max. | 1 μF |
| • with current outputs, max. | 750 Ω |
| • with current outputs, inductive load, max. | 10 mH |
| Cable length | |
| • shielded, max. | 800 m; for current, 200 m for voltage |
| Analog value generation for the outputs | |
| Integration and conversion time/resolution per channel | |
| • Resolution with overrange (bit including sign), max. | 16 bit |
| • Conversion time (per channel) | 125 μs; independent of number of activated channels |
| Settling time | |
| • for resistive load | 0.2 ms; see additional description in the manual |
| • for capacitive load | 1.8 ms; see additional description in the manual |
| • for inductive load | 2 ms; see additional description in the manual |
| Errors/accuracies | |
| Output ripple (relative to output range, bandwidth 0 to 50 kHz), (+/-) | 0.02 % |
| Linearity error (relative to output range), (+/-) | 0.015 % |
| Temperature error (relative to output range), (+/-) | 0.002 %/K |
| Crosstalk between the outputs, max. | -100 dB |
| Repeat accuracy in steady state at 25 °C (relative to output range), (+/-) | 0.005 % |
| note regarding accuracy | at temperatures below 0 °C, the figures for operating error and temperature error are doubled |
| Operational error limit in overall temperature range | |
| • Voltage, relative to output range, (+/-) | ±10 V; 0 V to 10 V: ±0.12%; 1 V to 5 V: ±0.1% |
| • Current, relative to output range, (+/-) | ±20 mA; 0 mA to 20 mA: ±0.2%; 4 mA to 20 mA: ±0.12% |
| Basic error limit (operational limit at 25 °C) | |
| • Voltage, relative to output range, (+/-) | 0.06 % |
| • Current, relative to output range, (+/-) | 0.1 % |
| Isochronous mode | |
| Execution and activation time (TCO), min. | 100 μs |
| Bus cycle time (TDP), min. | 250 μs |
| Interrupts/diagnostics/status information | |
| Diagnostics function | Yes |
| Substitute values connectable | Yes |
| Alarms | |
| • Diagnostic alarm | Yes |
| Diagnoses | |
| • Monitoring the supply voltage | Yes |
| • Wire-break | Yes; Only for output type "current" |
| • Short-circuit | Yes; Only for output type "voltage" |
| • Overflow/underflow | Yes |
| Diagnostics indication LED | |
| • RUN LED | Yes; green LED |
| • ERROR LED | Yes; red LED |
| • Monitoring of the supply voltage (PWR-LED) | Yes; green LED |
| • Channel status display | Yes; green LED |
| • for channel diagnostics | Yes; red LED |
| • for module diagnostics | Yes; red LED |

| Potential separation | | | |
|---|---|---------|----------------|
| Potential separation channels | | | |
| • between the channels | Yes | | |
| • between the channels, in groups of | 1 | | |
| • between the channels and backplane bus | Yes | | |
| • Between the channels and load voltage L+ | Yes | | |
| Permissible potential difference | | | |
| between different circuits | 60 V DC/30 V AC; insulation rated for 120 V AC basic insulation: between the channels and the supply voltage L+; between the channels and the backplane bus; between the channels | | |
| Isolation | | | |
| Isolation tested with | 2 000 V DC between the channels and the supply voltage L+; 2 000 V DC between the channels and the backplane bus; 2 000 V DC between the channels; 707 V DC (type test) between the supply voltage L+ and the backplane bus | | |
| Standards, approvals, certificates | | | |
| Suitable for safety-related tripping of standard modules | Yes; From FS03 | | |
| Highest safety class achievable for safety-related tripping of standard modules | | | |
| • Performance level according to ISO 13849-1 | PL d | | |
| • Category according to ISO 13849-1 | Cat. 3 | | |
| • SIL acc. to IEC 62061 | SIL 2 | | |
| • remark on safety-oriented shutdown | https://support.industry.siemens.com/cs/de/en/view/39198632 | | |
| product functions / security / header | | | |
| signed firmware update | No | | |
| data integrity | No | | |
| Ambient conditions | | | |
| Ambient temperature during operation | | | |
| • horizontal installation, min. | -25 °C; From FS02 | | |
| • horizontal installation, max. | 60 °C | | |
| • vertical installation, min. | -25 °C; From FS02 | | |
| • vertical installation, max. | 40 °C | | |
| Dimensions | | | |
| Width | 35 mm | | |
| Height | 147 mm | | |
| Depth | 129 mm | | |
| Weights | | | |
| Weight, approx. | 300 g | | |
| Classifications | | | |
| | | Version | Classification |
| | eClass | 14 | 27-24-22-01 |
| | eClass | 12 | 27-24-22-01 |
| | eClass | 9.1 | 27-24-22-01 |
| | eClass | 9 | 27-24-22-01 |
| | eClass | 8 | 27-24-22-01 |
| | eClass | 7.1 | 27-24-22-01 |
| | eClass | 6 | 27-24-22-01 |
| | ETIM | 9 | EC001420 |
| | ETIM | 8 | EC001420 |
| | ETIM | 7 | EC001420 |
| | IDEA | 4 | 3562 |
| | UNSPSC | 15 | 32-15-17-05 |
| Approvals / Certificates | | | |
| General Product Approval | | | |



[Miscellaneous](#)



[KC](#)



For use in hazardous locations

[FM](#)



[FM](#)

[CCC-Ex](#)



[Type Examination Certificate](#)

| | |
|--------------------------------|-------------------|
| For use in hazardous locations | Marine / Shipping |
|--------------------------------|-------------------|



IECEX

[Miscellaneous](#)



ABS



BUREAU
VERITAS



DNV



LRS

| | |
|-------------------|-------------|
| Marine / Shipping | Environment |
|-------------------|-------------|

[NK / Nippon Kaiji Kyokai](#)



RINA



RMRS

[CCS \(China Classification Society\)](#)



KR
KOREAN REGISTER



EPD

Environment

Siemens
EcoTech



last modified:

5/14/2025 