

product type designation

CM 1542-5

communications module CM 1542-5 for connection of S7-1500 to PROFIBUS DP, DPV1 master or DP slave, S7 and PG/OP communication, data record routing, time-of-day synchronization, diagnostic



transfer rate	
transfer rate	
• at the 1st interface / according to PROFIBUS	9.6 kbit/s ... 12 Mbit/s
interfaces	
number of interfaces / according to Industrial Ethernet	0
number of electrical connections	
• at the 1st interface / according to PROFIBUS	1
type of electrical connection	
• at the 1st interface / according to PROFIBUS	9-pin Sub-D socket (RS485)
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	15 V
relative symmetrical tolerance / at DC	
• at 15 V	3 %
consumed current	
• from backplane bus / at DC / at 15 V / typical	0.2 A
power loss [W]	3 W
ambient conditions	
ambient temperature	
• for vertical installation / during operation	0 ... 40 °C
• for horizontally arranged busbars / during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-1500 single width
width	35 mm
height	142 mm
depth	129 mm
net weight	0.4 kg
fastening method	
• S7-1500 rail mounting	Yes
product features, product functions, product components / general	
number of units	
• per CPU / maximum	8
• note	depending on CPU type

performance data / open communication	
number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	30
data volume	
<ul style="list-style-type: none"> as user data per connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	240 byte
performance data / PROFIBUS DP	
service / as DP master	
<ul style="list-style-type: none"> DPV1 	Yes
number of DP slaves	
<ul style="list-style-type: none"> on DP master / operable 	125
data volume	
<ul style="list-style-type: none"> of the address range of the inputs / as DP master / total 	8192 byte
<ul style="list-style-type: none"> of the address range of the outputs / as DP master / total 	8192 byte
<ul style="list-style-type: none"> of the address range of the inputs / per DP slave 	244 byte
<ul style="list-style-type: none"> of the address range of the outputs / per DP slave 	244 byte
service / as DP slave	
<ul style="list-style-type: none"> DPV0 	Yes
<ul style="list-style-type: none"> DPV1 	Yes
data volume	
<ul style="list-style-type: none"> of the address range of the inputs / as DP slave / total 	240 byte
<ul style="list-style-type: none"> of the address range of the outputs / as DP slave / total 	240 byte
performance data / S7 communication	
number of possible connections / for S7 communication	
<ul style="list-style-type: none"> maximum 	48; depending on the system upper limit
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	48
performance data / telecontrol	
protocol / is supported	
<ul style="list-style-type: none"> TCP/IP 	No
product functions / management, configuration, engineering	
configuration software	
<ul style="list-style-type: none"> required 	STEP 7 Professional V12 (TIA Portal) or higher
identification & maintenance function	
<ul style="list-style-type: none"> I&M0 - device-specific information 	Yes
<ul style="list-style-type: none"> I&M1 - higher level designation/location designation 	Yes
product functions / diagnostics	
product function / web-based diagnostics	Yes; via S7-1500 CPU
product functions / time	
product function / pass on time synchronization	Yes
standards, specifications, approvals	
reference code	
<ul style="list-style-type: none"> according to IEC 81346-2:2019 	KEC
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
<ul style="list-style-type: none"> total 	115.52 kg
<ul style="list-style-type: none"> during manufacturing 	21.24 kg
<ul style="list-style-type: none"> during operation 	93.93 kg
<ul style="list-style-type: none"> after end of life 	0.35 kg
further information / internet links	
internet link	
<ul style="list-style-type: none"> to web page: selection aid TIA Selection Tool 	https://www.siemens.com/tstcloud
<ul style="list-style-type: none"> to website: Industrial communication 	https://www.siemens.com/simatic-net
<ul style="list-style-type: none"> to web page: SiePortal 	https://sieportal.siemens.com/
<ul style="list-style-type: none"> to website: Image database 	https://www.automation.siemens.com/bilddb
<ul style="list-style-type: none"> to website: CAX-Download-Manager 	https://siemens.com/cax
<ul style="list-style-type: none"> to website: Industry Online Support 	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks.

In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Approvals / Certificates

General Product Approval



[Declaration of Conformity](#)



General Product Approval

For use in hazardous locations

Environment



[FM](#)

[CCC-Ex](#)

[Confirmation](#)

Environment



last modified:

2/18/2025