



Figure similar

SIPLUS S7-300 CPU 317F-2DP based on 6ES7317-6FF04-0AB0 with conformal coating, -25...+60 °C, central processing unit with 1.5 MB work memory, 1st interface MPI/DP 12 Mbps, 2nd interface DP master/ slave, Micro Memory Card required can be used with software package S7 Distributed Safety V5.2 SP1 or higher

| General information | |
|---|---|
| Product type designation | CPU 317F-2 DP |
| based on | 6ES7317-6FF04-0AB0 |
| Engineering with | |
| • Programming package | STEP 7 V5.5 + SP1 or higher or STEP 7 V5.2 + SP1 or higher with HSP 202 + Distributed Safety |
| Supply voltage | |
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 19.2 V |
| permissible range, upper limit (DC) | 28.8 V |
| external protection for power supply lines (recommendation) | 2 A min. |
| Input current | |
| Current consumption (rated value) | 870 mA |
| Current consumption (in no-load operation), typ. | 120 mA |
| Inrush current, typ. | 4 A |
| I ² t | 1 A ² s |
| Power loss | |
| Power loss, typ. | 4.5 W |
| Memory | |
| Work memory | |
| • integrated | 1 536 kbyte |
| • expandable | No |
| Load memory | |
| • Plug-in (MMC) | Yes |
| • Plug-in (MMC), max. | 8 Mbyte |
| • Data management on MMC (after last programming), min. | 10 a |
| Backup | |
| • present | Yes; Guaranteed by MMC (maintenance-free) |
| • without battery | Yes; Program and data |
| CPU processing times | |
| for bit operations, typ. | 0.025 µs |
| for word operations, typ. | 0.03 µs |
| for fixed point arithmetic, typ. | 0.04 µs |
| for floating point arithmetic, typ. | 0.16 µs |
| CPU-blocks | |
| Number of blocks (total) | 2 048; (DBs, FCs, FBs); the maximum number of loadable blocks can be reduced by the MMC used. |
| DB | |
| • Number, max. | 2 048; Number range: 1 to 16000 |

| | |
|---|--|
| • Size, max. | 64 kbyte |
| FB | |
| • Number, max. | 2 048; Number range: 0 to 7999 |
| • Size, max. | 64 kbyte |
| FC | |
| • Number, max. | 2 048; Number range: 0 to 7999 |
| • Size, max. | 64 kbyte |
| OB | |
| • Number, max. | see instruction list |
| • Size, max. | 64 kbyte |
| • Number of free cycle OBs | 1; OB 1 |
| • Number of time alarm OBs | 1; OB 10 |
| • Number of delay alarm OBs | 2; OB 20, 21 |
| • Number of cyclic interrupt OBs | 4; OB 32, 33, 34, 35 |
| • Number of process alarm OBs | 1; OB 40 |
| • Number of DPV1 alarm OBs | 3; OB 55, 56, 57 |
| • Number of isochronous mode OBs | 1; OB 61 |
| • Number of startup OBs | 1; OB 100 |
| • Number of asynchronous error OBs | 5; OB 80, 82, 85, 86, 87 |
| • Number of synchronous error OBs | 2; OB 121, 122 |
| Nesting depth | |
| • per priority class | 16 |
| • additional within an error OB | 4 |
| Counters, timers and their retentivity | |
| S7 counter | |
| • Number | 512 |
| Retentivity | |
| — adjustable | Yes |
| — preset | Z 0 to Z 7 |
| Counting range | |
| — lower limit | 0 |
| — upper limit | 999 |
| IEC counter | |
| • present | Yes |
| • Type | SFB |
| • Number | Unlimited (limited only by RAM capacity) |
| S7 times | |
| • Number | 512 |
| Retentivity | |
| — adjustable | Yes |
| — preset | No retentivity |
| Time range | |
| — lower limit | 10 ms |
| — upper limit | 9 990 s |
| IEC timer | |
| • present | Yes |
| • Type | SFB |
| • Number | Unlimited (limited only by RAM capacity) |
| Data areas and their retentivity | |
| Retentive data area (incl. timers, counters, flags), max. | 256 kbyte |
| Flag | |
| • Size, max. | 4 096 byte |
| • Retentivity available | Yes; From MB 0 to MB 4 095 |
| • Retentivity preset | MB 0 to MB 15 |
| • Number of clock memories | 8; 1 memory byte |
| Data blocks | |
| • Retentivity adjustable | Yes; via non-retain property on DB |
| • Retentivity preset | Yes |
| Local data | |
| • per priority class, max. | 32 768 byte; Max. 2048 bytes per block |

| | |
|---|---|
| Address area | |
| I/O address area | |
| • Inputs | 8 192 byte |
| • Outputs | 8 192 byte |
| of which distributed | |
| — Inputs | 8 192 byte |
| — Outputs | 8 192 byte |
| Process image | |
| • Inputs | 8 192 byte |
| • Outputs | 8 192 byte |
| • Inputs, adjustable | 8 192 byte |
| • Outputs, adjustable | 8 192 byte |
| • Inputs, default | 1 024 byte |
| • Outputs, default | 1 024 byte |
| Subprocess images | |
| • Number of subprocess images, max. | 1 |
| Digital channels | |
| • Inputs | 65 536 |
| — of which central | 1 024 |
| • Outputs | 65 536 |
| — of which central | 1 024 |
| Analog channels | |
| • Inputs | 4 096 |
| — of which central | 256 |
| • Outputs | 4 096 |
| — of which central | 256 |
| Hardware configuration | |
| Number of expansion units, max. | 3 |
| Number of DP masters | |
| • integrated | 2 |
| • via CP | 4 |
| Number of operable FMs and CPs (recommended) | |
| • FM | 8 |
| • CP, PtP | 8 |
| • CP, LAN | 10 |
| Rack | |
| • Racks, max. | 4 |
| • Modules per rack, max. | 8 |
| Time of day | |
| Clock | |
| • Hardware clock (real-time) | Yes |
| • retentive and synchronizable | Yes |
| • Backup time | 6 wk; At 40 °C ambient temperature |
| • Deviation per day, max. | 10 s; Typ.: 2 s |
| • Behavior of the clock following POWER-ON | Clock continues running after POWER OFF |
| • Behavior of the clock following expiry of backup period | the clock continues at the time of day it had when power was switched off |
| Operating hours counter | |
| • Number | 4 |
| • Number/Number range | 0 to 3 |
| • Range of values | 0 to 2 ³¹ hours (when using SFC 101) |
| • Granularity | 1 h |
| • retentive | Yes; Must be restarted at each restart |
| Clock synchronization | |
| • supported | Yes |
| • to MPI, master | Yes |
| • on MPI, device | Yes |
| • to DP, master | Yes; With DP slave only slave clock |
| • on DP, device | Yes |
| • in AS, master | Yes |
| • in AS, device | Yes |

| | |
|--|--|
| • on Ethernet via NTP | No |
| Digital inputs | |
| Number of digital inputs | 0 |
| Digital outputs | |
| Number of digital outputs | 0 |
| Analog inputs | |
| Number of analog inputs | 0 |
| Interfaces | |
| Number of PROFINET interfaces | 0 |
| Number of RS 485 interfaces | 2 |
| Number of RS 422 interfaces | 0 |
| 1. Interface | |
| Interface type | Integrated RS 485 interface |
| Isolated | Yes |
| Interface types | |
| • RS 485 | Yes |
| • Output current of the interface, max. | 200 mA |
| Protocols | |
| • MPI | Yes |
| • PROFIBUS DP master | Yes |
| • PROFIBUS DP device | Yes |
| • Point-to-point connection | No |
| MPI | |
| • Transmission rate, max. | 12 Mbit/s |
| Services | |
| — PG/OP communication | Yes |
| — Routing | Yes |
| — Global data communication | Yes |
| — S7 basic communication | Yes |
| — S7 communication | Yes; Only server, configured on one side |
| — S7 communication, as client | No; but via CP and loadable FB |
| — S7 communication, as server | Yes |
| PROFIBUS DP master | |
| • Transmission rate, max. | 12 Mbit/s |
| • max. number of DP devices | 124 |
| Services | |
| — PG/OP communication | Yes |
| — Routing | Yes |
| — Global data communication | No |
| — S7 basic communication | Yes; I blocks only |
| — S7 communication | Yes; Only server, configured on one side |
| — S7 communication, as client | No |
| — S7 communication, as server | Yes |
| — Equidistance | Yes |
| — Isochronous mode | No |
| — SYNC/FREEZE | Yes |
| — activation/deactivation of DP devices | Yes |
| — max. number of DP devices that can be activated/deactivated at the same time | 8 |
| — Direct data exchange (slave-to-slave communication) | Yes; as subscriber |
| — DPV1 | Yes |
| Address area | |
| — Inputs, max. | 8 kbyte |
| — Outputs, max. | 8 kbyte |
| User data per DP device | |
| — Inputs, max. | 244 byte |
| — Outputs, max. | 244 byte |
| 1st interface / PROFIBUS DP device / header | |
| • Transmission rate, max. | 12 Mbit/s |
| • automatic baud rate search | Yes; only with passive interface |

| | |
|--|--|
| • Address area, max. | 32 |
| • User data per address area, max. | 32 byte |
| Services | |
| — PG/OP communication | Yes |
| — Routing | Yes; Only with active interface |
| — Global data communication | No |
| — S7 basic communication | No |
| — S7 communication | Yes; Only server, configured on one side |
| — S7 communication, as client | No |
| — S7 communication, as server | Yes; Connection configured on one side only |
| — Direct data exchange (slave-to-slave communication) | Yes |
| — DPV1 | No |
| Transfer memory | |
| — Inputs | 244 byte |
| — Outputs | 244 byte |
| 2. Interface | |
| Interface type | Integrated RS 485 interface |
| Isolated | Yes |
| Interface types | |
| • RS 485 | Yes |
| • Output current of the interface, max. | 200 mA |
| Protocols | |
| • MPI | No |
| • PROFIBUS DP master | Yes |
| • PROFIBUS DP device | Yes |
| • Point-to-point connection | No |
| PROFIBUS DP master | |
| • Transmission rate, max. | 12 Mbit/s |
| • max. number of DP devices | 124 |
| Services | |
| — PG/OP communication | Yes |
| — Routing | Yes |
| — Global data communication | No |
| — S7 basic communication | Yes; I blocks only |
| — S7 communication | Yes; Only server, configured on one side |
| — S7 communication, as client | No; but via CP and loadable FB |
| — S7 communication, as server | Yes |
| — Equidistance | Yes |
| — Isochronous mode | Yes; OB 61 |
| — SYNC/FREEZE | Yes |
| — activation/deactivation of DP devices | Yes |
| — max. number of DP devices that can be activated/deactivated at the same time | 8 |
| — Direct data exchange (slave-to-slave communication) | Yes; as subscriber |
| — DPV1 | Yes |
| Address area | |
| — Inputs, max. | 8 192 byte |
| — Outputs, max. | 8 192 byte |
| User data per DP device | |
| — Inputs, max. | 244 byte |
| — Outputs, max. | 244 byte |
| 2nd interface / PROFIBUS DP device / header | |
| • GSD file | The latest GSD file is available on the Internet (http://www.siemens.com/profibus-gsd) |
| • Transmission rate, max. | 12 Mbit/s |
| • automatic baud rate search | Yes; only with passive interface |
| • Address area, max. | 32 |
| • User data per address area, max. | 32 byte |
| Services | |
| — PG/OP communication | Yes |

| | |
|---|--|
| — Routing | Yes; Only with active interface |
| — Global data communication | No |
| — S7 basic communication | No |
| — S7 communication | Yes; Only server, configured on one side |
| — S7 communication, as client | No; but via CP and loadable FB |
| — S7 communication, as server | Yes |
| — Direct data exchange (slave-to-slave communication) | Yes |
| — DPV1 | No |
| Transfer memory | |
| — Inputs | 244 byte |
| — Outputs | 244 byte |
| Protocols | |
| PROFIsafe | No |
| communication functions / header | |
| PG/OP communication | Yes |
| Data record routing | Yes |
| Global data communication | |
| • supported | Yes |
| • Number of GD loops, max. | 8 |
| • Number of GD packets, max. | 8 |
| • Number of GD packets, transmitter, max. | 8 |
| • Number of GD packets, receiver, max. | 8 |
| • Size of GD packets, max. | 22 byte |
| • Size of GD packet (of which consistent), max. | 22 byte |
| S7 basic communication | |
| • supported | Yes |
| • User data per job, max. | 76 byte |
| • User data per job (of which consistent), max. | 76 byte; 76 bytes (with X_SEND or X_RCV); 64 bytes (with X_PUT or X_GET as server) |
| S7 communication | |
| • supported | Yes |
| • as server | Yes |
| • as client | Yes; Via CP and loadable FB |
| • User data per job, max. | See online help of STEP 7 (shared parameters of the SFBs/FBs and of the SFCs/FCs of S7 Communication) |
| S5 compatible communication | |
| • supported | Yes; via CP and loadable FC |
| Number of connections | |
| • overall | 32 |
| • usable for PG communication | 31 |
| — reserved for PG communication | 1 |
| — adjustable for PG communication, min. | 1 |
| — adjustable for PG communication, max. | 31 |
| • usable for OP communication | 31 |
| — reserved for OP communication | 1 |
| — adjustable for OP communication, min. | 1 |
| — adjustable for OP communication, max. | 31 |
| • usable for S7 basic communication | 30 |
| — reserved for S7 basic communication | 0 |
| — adjustable for S7 basic communication, min. | 0 |
| — adjustable for S7 basic communication, max. | 30 |
| • usable for routing | X1 as a MPI, max. 10; X1 as DP Master max. 24; X1 as DP Slave (active) max. 14; X2 as DP Master max. 24; X2 as DP Slave (active) max. 14 |
| S7 message functions | |
| Number of login stations for message functions, max. | 32; Depending on the configured connections for PG/OP and S7 basic communication |
| Process diagnostic messages | Yes |
| simultaneously active Alarm_S blocks, max. | 300 |
| Test commissioning functions | |
| Status block | Yes; Up to 2 simultaneously |
| Single step | Yes |

| | |
|--|---|
| Number of breakpoints | 4 |
| Status/control | |
| • Status/control variable | Yes |
| • Variables | Inputs, outputs, memory bits, DB, times, counters |
| • Number of variables, max. | 30 |
| — of which status variables, max. | 30 |
| — of which control variables, max. | 14 |
| Forcing | |
| • Forcing | Yes |
| • Forcing, variables | Inputs, outputs |
| • Number of variables, max. | 10 |
| Diagnostic buffer | |
| • present | Yes |
| • Number of entries, max. | 500 |
| — adjustable | No |
| — of which powerfail-proof | 100; Only the last 100 entries are retained |
| • Number of entries readable in RUN, max. | 499 |
| — adjustable | Yes; From 10 to 499 |
| — preset | 10 |
| Service data | |
| • can be read out | Yes |
| Standards, approvals, certificates | |
| CE mark | Yes |
| UL approval | Yes |
| KC approval | Yes |
| EAC (formerly Gost-R) | Yes |
| Use in hazardous areas | |
| • ATEX | Yes |
| Ambient conditions | |
| Ambient temperature during operation | |
| • min. | -25 °C; = Tmin |
| • max. | 60 °C; = Tmax |
| Ambient temperature during storage/transportation | |
| • min. | -40 °C |
| • max. | 70 °C |
| Altitude during operation relating to sea level | |
| • Installation altitude above sea level, max. | 2 000 m |
| • Ambient air temperature-barometric pressure-altitude | Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) |
| Relative humidity | |
| • With condensation, tested in accordance with IEC 60068-2-38, max. | 100 %; RH incl. condensation/frost (no commissioning under condensation conditions) |
| Resistance | |
| Use in stationary industrial systems | |
| — to biologically active substances according to EN 60721-3-3 | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request |
| — to chemically active substances according to EN 60721-3-3 | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-3 | Yes; Class 3S4 incl. sand, dust, * |
| Use on ships/at sea | |
| — to biologically active substances according to EN 60721-3-6 | Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request |
| — to chemically active substances according to EN 60721-3-6 | Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-6 | Yes; Class 6S3 incl. sand, dust; * |
| Usage in industrial process technology | |
| — Against chemically active substances acc. to EN 60654-4 | Yes; Class 3 (excluding trichlorethylene) |
| — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04 | Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil) |
| Remark | |
| — Note regarding classification of environmental | * The supplied plug covers must remain in place over the unused interfaces |

conditions acc. to EN 60721, EN 60654-4 and
ANSI/ISA-71.04

during operation!

configuration / header

| | |
|---|--|
| Configuration software | |
| • STEP 7 | Yes; STEP 7 V5.5 + SP1 or higher or STEP 7 V5.3 + SP2 or higher with HSP 203 |
| • STEP 7 Lite | No |
| configuration / programming / header | |
| • Command set | see instruction list |
| • Nesting levels | 8 |
| • System functions (SFC) | see instruction list |
| • System function blocks (SFB) | see instruction list |
| Programming language | |
| — LAD | Yes |
| — FBD | Yes |
| — STL | Yes |
| — SCL | Yes |
| — CFC | Yes |
| — GRAPH | Yes |
| — HiGraph® | Yes |
| Know-how protection | |
| • User program protection/password protection | Yes |
| • Block encryption | Yes; With S7 block Privacy |

Dimensions

| | |
|--------|--------|
| Width | 40 mm |
| Height | 125 mm |
| Depth | 130 mm |

Weights

| | |
|-----------------|-------|
| Weight, approx. | 360 g |
|-----------------|-------|

Classifications

| | Version | Classification |
|--------|---------|----------------|
| eClass | 14 | 27-24-22-07 |
| eClass | 12 | 27-24-22-07 |
| eClass | 9.1 | 27-24-22-07 |
| eClass | 9 | 27-24-22-07 |
| eClass | 8 | 27-24-22-07 |
| eClass | 7.1 | 27-24-22-07 |
| eClass | 6 | 27-24-22-07 |
| ETIM | 9 | EC000236 |
| ETIM | 8 | EC000236 |
| ETIM | 7 | EC000236 |
| IDEA | 4 | 3565 |
| UNSPSC | 15 | 32-15-17-05 |

Approvals / Certificates

General Product Approval

[Miscellaneous](#)



[Manufacturer Declaration](#)



EMV

[KC](#)



For use in hazardous locations



Functional Safety

[CCC-Ex](#)





last modified:

12/8/2024 