



SIPLUS NET CP 343-1 Lean based on 6GK7343-1CX10-0XE0 with conformal coating, -25...+60 °C, communications processor for connection of SIMATIC S7-300 to Industrial Ethernet via TCP/IP and UDP, multicast, send/receive with and without RFC1006, fetch/ write, S7 communication (server) PROFINET IO device integrated 2-port switch ERTEC 200, module replacement without PG, SNMP diagnostics, initialization via LAN,

| transfer rate | |
|--|--|
| transfer rate | |
| • at the 1st interface | 10 ... 100 Mbit/s |
| interfaces | |
| number of interfaces / according to Industrial Ethernet | 2 |
| number of electrical connections | |
| • at the 1st interface / according to Industrial Ethernet | 2 |
| • for power supply | 1 |
| type of electrical connection | |
| • of Industrial Ethernet interface | RJ45 port |
| • at the 1st interface / according to Industrial Ethernet | RJ45 port |
| type of electrical connection | |
| • for power supply | 2-pole plugable terminal block |
| supply voltage, current consumption, power loss | |
| type of voltage / of the supply voltage | DC |
| supply voltage / 1 / from backplane bus | 5 V |
| supply voltage | 24 V |
| supply voltage / external | 24 V |
| supply voltage / external / at DC / rated value | 24 V |
| relative positive tolerance / at DC / at 24 V | 20 % |
| relative negative tolerance / at DC / at 24 V | 15 % |
| consumed current | |
| • from backplane bus / at DC / at 5 V / typical | 0.2 A |
| • from external supply voltage / at DC / at 24 V / typical | 0.16 A |
| • from external supply voltage / at DC / at 24 V / maximum | 0.2 A |
| power loss [W] | 5.8 W |
| ambient conditions | |
| ambient temperature | |
| • for vertical installation / during operation | -25 ... +40 °C |
| • for horizontally arranged busbars / during operation | -25 ... +60 °C |
| • during storage | -40 ... +70 °C |
| • during transport | -40 ... +70 °C |
| installation altitude / at height above sea level / maximum | 5000 m |
| ambient condition / relating to ambient temperature - air pressure - installation altitude | Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m) |
| relative humidity | |
| • with condensation / according to IEC 60068-2-38 / maximum | 100 %; RH including condensation/frost (no commissioning when condensation is present), horizontal installation |
| chemical resistance / to commercially available cooling lubricants | Yes; incl. airborne diesel and oil droplets |

| | |
|---|---|
| resistance to biologically active substances | |
| • conformity according to EN 60721-3-3 | Yes; Class 3B2 mold and fungal spores (excluding fauna), Class 3B3 on request |
| • conformity according to EN 60721-3-6 | Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna) |
| resistance to chemically active substances | |
| • conformity according to EN 60721-3-3 | Yes; Class 3C4 (RH < 75 %) incl. salt spray in accordance with EN 60068-2-52 (Severity 3). The supplied plug covers must remain in place on the unused interfaces during operation. |
| • conformity according to EN 60721-3-6 | Yes |
| resistance to mechanically active substances | |
| • conformity according to EN 60721-3-3 | Yes; Class 3S4 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation. |
| • conformity according to EN 60721-3-6 | Yes; Class 6S3 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation. |
| coating / for equipped printed circuit board / according to EN 61086 | Yes; Class 2 for high availability |
| type of coating / protection against pollution according to EN 60664-3 | Yes; Protection of the type 1 |
| type of test / of the coating / according to MIL-I-46058C | Yes; Coating discoloration during service life possible |
| product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A | Yes; Conformal coating, class A |
| protection class IP | IP20 |
| design, dimensions and weights | |
| module format | Compact module S7-300 single width |
| width | 40 mm |
| height | 125 mm |
| depth | 120 mm |
| net weight | 0.22 kg |
| fastening method | |
| • S7-300 rail mounting | Yes |
| performance data / open communication | |
| number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum | 8 |
| data volume | |
| • as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum | 8 Kibyte |
| • as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum | 8 Kibyte |
| • as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum | 2 Kibyte |
| number of Multicast stations | 8 |
| performance data / S7 communication | |
| number of possible connections / for S7 communication | |
| • maximum | 4 |
| service | |
| • of SIMATIC communication / as server | Yes |
| performance data / multi-protocol mode | |
| number of active connections / with multi-protocol mode | 12 |
| performance data / PROFINET communication / as PN IO controller | |
| product function / PROFINET IO controller | No |
| performance data / PROFINET communication / as PN IO device | |
| product function / PROFINET IO device | Yes |
| data volume | |
| • as user data for input variables / as PROFINET IO device / maximum | 512 byte |
| • as user data for output variables / as PROFINET IO device / maximum | 512 byte |
| • as user data for input variables / for each sub-module as PROFINET IO device | 240 byte |
| • as user data for output variables / for each sub-module as PROFINET IO device | 240 byte |
| • as user data for the consistency area for each sub-module | 240 byte |

| | |
|---|---|
| number of submodules / per PROFINET IO-Device | 32 |
| performance data / telecontrol | |
| protocol / is supported | |
| • TCP/IP | Yes |
| product functions / management, configuration, engineering | |
| product function / MIB support | Yes |
| protocol / is supported | |
| • SNMP v1 | Yes |
| • DCP | Yes |
| • LLDP | Yes |
| configuration software | |
| • required | STEP 7 V5.4 or higher / STEP 7 Professional V11 (TIA Portal) or higher |
| identification & maintenance function | |
| • I&M0 - device-specific information | Yes |
| • I&M1 - higher level designation/location designation | Yes |
| product functions / diagnostics | |
| product function / web-based diagnostics | Yes |
| product functions / switch | |
| product feature / switch | Yes |
| product function | |
| • switch-managed | No |
| • with IRT / PROFINET IO switch | No |
| • configuration with STEP 7 | Yes |
| product functions / redundancy | |
| product function | |
| • ring redundancy | Yes |
| • redundancy manager | No |
| protocol / is supported / Media Redundancy Protocol (MRP) | Yes |
| product functions / security | |
| product function | |
| • password protection for Web applications | No |
| • ACL - IP-based | Yes |
| • ACL - IP-based for PLC/routing | No |
| • switch-off of non-required services | Yes |
| • blocking of communication via physical ports | Yes |
| • log file for unauthorized access | No |
| product functions / time | |
| product function / SICLOCK support | Yes |
| product function / pass on time synchronization | Yes |
| protocol / is supported | |
| • NTP | Yes |
| standards, specifications, approvals | |
| reference code | |
| • according to IEC 81346-2:2019 | KEC |
| further information / internet links | |
| internet link | |
| • to website: Selection guide for cables and connectors | https://support.industry.siemens.com/cs/ww/en/view/109766358 |
| • to web page: selection aid TIA Selection Tool | https://www.siemens.com/tstcloud |
| • to website: Industrial communication | https://www.siemens.com/simatic-net |
| • to web page: SiePortal | https://sieportal.siemens.com/ |
| • to website: Image database | https://www.automation.siemens.com/bilddb |
| • to website: CAX-Download-Manager | https://siemens.com/cax |
| • to website: Industry Online Support | https://support.industry.siemens.com |
| security information | |
| security information | Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected |

to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Approvals / Certificates

General Product Approval

[Miscellaneous](#)



[Manufacturer Declaration](#)



[KC](#)

EMV For use in hazardous locations



[CCC-Ex](#)



last modified: 2/28/2025 