



SIPLUS NET TIM 3V-IE based on 6NH7800-3BA00 with conformal coating, - 25...+70 °C, communications module for SIMATIC S7-300 and C7; with one RS-232 interface for SINAUT communication via a classic WAN and an RJ45 interface for SINAUT communication via an IP-based network (WAN or LAN)

transfer rate

transfer rate	
• for Industrial Ethernet	10 ... 100 Mbit/s
• according to RS 232	50 ... 38400 bit/s

interfaces

number of interfaces / according to Industrial Ethernet	1
number of electrical connections	
• for external data transmission / according to RS 232	1
• for power supply	1
type of electrical connection	
• of Industrial Ethernet interface	RJ45 port
type of electrical connection	
• at interface 1 / for external data transmission	9 pin Sub-D-connector (RS232)
• for power supply	2-pole plugable terminal block
design of the removable storage	
• C-PLUG	No

supply voltage, current consumption, power loss

type of voltage / of the supply voltage	DC
supply voltage	24 V
supply voltage	20.4 ... 28.8 V
supply voltage / external / at DC / rated value	24 V
supply voltage / external / at DC / rated value	20.4 ... 28.8 V
relative symmetrical tolerance / at DC	
• at 5 V	5 %
relative positive tolerance / at DC / at 24 V	5 %
relative negative tolerance / at DC / at 24 V	5 %
consumed current	
• from backplane bus / at DC / at 24 V / maximum	0.2 A
• from external supply voltage / at DC / at 24 V / maximum	0.2 A
power loss [W]	5.8 W
product extension / optional / backup battery	No

ambient conditions

ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
installation altitude / at height above sea level / maximum	5000 m
ambient condition / relating to ambient temperature - air pressure - installation altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
relative humidity	

<ul style="list-style-type: none"> • with condensation / according to IEC 60068-2-38 / maximum 	100 %; RH including condensation/frost (no commissioning when condensation is present), horizontal installation
chemical resistance / to commercially available cooling lubricants	Yes; incl. airborne diesel and oil droplets
resistance to biologically active substances <ul style="list-style-type: none"> • conformity according to EN 60721-3-3 	Yes; Class 3B2 mold and fungal spores (excluding fauna), Class 3B3 on request
<ul style="list-style-type: none"> • conformity according to EN 60721-3-6 	Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)
resistance to chemically active substances <ul style="list-style-type: none"> • conformity according to EN 60721-3-3 	Yes; Class 3C4 (RH < 75 %) incl. salt spray in accordance with EN 60068-2-52 (Severity 3). The supplied plug covers must remain in place on the unused interfaces during operation.
<ul style="list-style-type: none"> • conformity according to EN 60721-3-6 	Yes
resistance to mechanically active substances <ul style="list-style-type: none"> • conformity according to EN 60721-3-3 	Yes; Class 3S4 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
<ul style="list-style-type: none"> • conformity according to EN 60721-3-6 	Yes; Class 6S3 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
coating / for equipped printed circuit board / according to EN 61086	Yes; Class 2 for high availability
type of coating / protection against pollution according to EN 60664-3	Yes; Protection of the type 1
type of test / of the coating / according to MIL-I-46058C	Yes; Coating discoloration during service life possible
product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, class A
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-300 single width
width	40 mm
height	125 mm
depth	120 mm
net weight	0.2 kg
product features, product functions, product components / general	
number of units <ul style="list-style-type: none"> • per CPU / maximum 	1
wire length <ul style="list-style-type: none"> • with RS 232 interface / maximum 	6 m
performance data / S7 communication	
number of possible connections / for S7 communication <ul style="list-style-type: none"> • maximum • with PG connections / maximum • with OP connections / maximum 	12 4 8
service <ul style="list-style-type: none"> • SINAUT ST7 via S7 communication • PG/OP communication 	Yes Yes
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	12
performance data / telecontrol	
suitability for use <ul style="list-style-type: none"> • node station • substation • TIM control center 	No Yes Yes
protocol / is supported <ul style="list-style-type: none"> • SINAUT ST1 protocol • SINAUT ST7 protocol 	Yes Yes
storage capacity <ul style="list-style-type: none"> • note 	TD7onCPU: at least 20 KB, actual requirement determined by data volume and functional scope TD7onTIM: 0 bytes in most favorable case
product feature / buffered message frame memory	No
transmission format <ul style="list-style-type: none"> • for SINAUT ST1 protocol with polling / 11 bit • for SINAUT ST1 protocol with spontaneous / 10-bit or 11-bit 	Yes Yes

<ul style="list-style-type: none"> • for SINAUT ST7 protocol with multi-master polling / 10-bit • for SINAUT ST7 protocol with polling or spontaneous / 10-bit or 11-bit 	Yes
operating mode for scanning of data transmission	Yes
<ul style="list-style-type: none"> • with dedicated line/radio link / with SINAUT ST1 protocol • with dedicated line/radio link / with SINAUT ST7 protocol 	Polling, polling with time slot procedure
<ul style="list-style-type: none"> • with dial-up network / with SINAUT ST1 protocol • with dial-up network / with SINAUT ST7 protocol 	Polling, polling with time slot procedure, multi-master polling with time slot procedure
hamming distance	spontaneous
<ul style="list-style-type: none"> • for SINAUT ST1 protocol • for SINAUT ST7 protocol 	spontaneous

product functions / management, configuration, engineering

configuration software	SINAUT ST7 ES
<ul style="list-style-type: none"> • required • for CPU configuring / required / SINAUT TD7 block library for CPU • for PG configuring / required / SINAUT ST7 configuration software for PG 	Yes
storage location / of TIM configuration data	Yes
	on the CPU

product functions / security

operating mode / Virtual Private Network (VPN)	Yes
type of authentication / with Virtual Private Network / PSK	Yes

standards, specifications, approvals

reference code	
<ul style="list-style-type: none"> • according to IEC 81346-2:2019 	KEC

further information / internet links

internet link	
<ul style="list-style-type: none"> • to website: Selection guide for cables and connectors • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to web page: SiePortal • to website: Image database • to website: CAX-Download-Manager • to website: Industry Online Support 	https://support.industry.siemens.com/cs/ww/en/view/109766358 https://www.siemens.com/tstcloud https://www.siemens.com/simatic-net https://sieportal.siemens.com/ https://www.automation.siemens.com/bilddb https://siemens.com/cax https://support.industry.siemens.com

security information

security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)</p>
----------------------	--

Approvals / Certificates

General Product Approval	EMV
--------------------------	-----

[Miscellaneous](#)

[Manufacturer Declaration](#)



[KC](#)



last modified:

2/28/2025