



SITOP PSU400M/DC/DC/600V/24V/20A

SITOP PSU400M 20 A DC/DC converter input: 600 V DC output: 24 V DC/20 A

input	
type of the power supply network	DC voltage
supply voltage at AC	startup from 340 V DC; derating necessary at 300 ... 400 V DC and 824 ... 900 V DC
supply voltage at DC	600 ... 600 V
input voltage at DC	300 ... 900 V
overvoltage overload capability	Shutdown at $V_{in} > 900$ V DC
input current at DC	
• at rated input voltage 600 V	0.85 A
current limitation of inrush current at 25 °C maximum	8 A
I ² t value maximum	0.02 A ² ·s
fuse protection type	yes, cut-off capacity 20 kA; L/R < 2 ms ("+" and "-" input)
output	
voltage curve at output	Controlled, isolated DC voltage
output voltage at DC rated value	24 V
output voltage	
• at output 1 at DC rated value	24 V
output voltage adjustable	Yes; via potentiometer
adjustable output voltage	24 ... 28.8 V; max. 480 W
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage	
• on slow fluctuation of input voltage	0.3 %
• on slow fluctuation of ohm loading	0.3 %
residual ripple	
• maximum	150 mV
• typical	30 mV
voltage peak	
• maximum	200 mV
• typical	100 mV
display version for normal operation	Green LED for 24 V OK, green flashing LED for start delay
type of signal at output	Relay contact (NO contact, rating 60 V DC/ 0.3 A; 30 V DC/1 A) for 24 V OK
behavior of the output voltage when switching on	No overshoot of V_{out} (soft start)
response delay maximum	0.1 s; 10 s adjustable using switch
voltage increase time of the output voltage	
• maximum	150 ms
output current	
• rated value	20 A
• rated range	0 ... 20 A; +60 ... +70 °C: Derating 5.5%/K
supplied active power typical	480 W
short-term overload current	

<ul style="list-style-type: none"> • on short-circuiting during the start-up typical • at short-circuit during operation typical 	40 A 60 A
duration of overloading capability for excess current	
<ul style="list-style-type: none"> • on short-circuiting during the start-up • at short-circuit during operation 	150 ms 25 ms
constant overload current	
<ul style="list-style-type: none"> • on short-circuiting during the start-up typical 	23 A
bridging of equipment	Yes; switchable characteristic
number of parallel-switched equipment resources for increasing the power	2
efficiency	
efficiency in percent	95 %
power loss [W]	
<ul style="list-style-type: none"> • at rated output voltage for rated value of the output current typical 	25 W
closed-loop control	
relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical	1.5 %
relative control precision of the output voltage load step of resistive load 50/100/50 % typical	1.5 %
setting time	
<ul style="list-style-type: none"> • load step 50 to 100% typical • load step 100 to 50% typical 	1 ms 1 ms
setting time	
<ul style="list-style-type: none"> • maximum 	5 ms
protection and monitoring	
design of the overvoltage protection	< 33 V
property of the output short-circuit proof	Yes
design of short-circuit protection	Alternatively, constant current characteristic approx. 22 A or latching shutdown
<ul style="list-style-type: none"> • typical 	22 A
overcurrent overload capability	
<ul style="list-style-type: none"> • in normal operation 	overload capability 150 % I _{out} rated up to 5 s/min
enduring short circuit current RMS value	
<ul style="list-style-type: none"> • typical 	22 A
display version for overload and short circuit	LED yellow for "overload", LED red for "latching shutdown", red LED flashing for "Overtemperature"
safety	
galvanic isolation between input and output	Yes
galvanic isolation	Protective extra low output voltage V _{out} according to EN 60950-1 and EN 50178
operating resource protection class	Class I
protection class IP	IP20
EMC	
standard	
<ul style="list-style-type: none"> • for emitted interference • for mains harmonics limitation • for interference immunity 	EN 55022 Class A (emission) - EN 61000-6-2
standards, specifications, approvals	
certificate of suitability	
<ul style="list-style-type: none"> • CE marking • UL approval • CSA approval • UKCA marking • EAC approval • Regulatory Compliance Mark (RCM) • NEC Class 2 	Yes Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259 Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259 Yes Yes Yes No
type of certification	
<ul style="list-style-type: none"> • CB-certificate 	Yes
MTBF at 40 °C	622 277 h
standards, specifications, approvals hazardous environments	
certificate of suitability	
<ul style="list-style-type: none"> • IECEx 	No

<ul style="list-style-type: none"> • ATEX • ULhazloc approval • cCSAus, Class 1, Division 2 • FM registration 	No No No No
standards, specifications, approvals marine classification	
shipbuilding approval	Yes
Marine classification association	
<ul style="list-style-type: none"> • American Bureau of Shipping Europe Ltd. (ABS) • French marine classification society (BV) • Det Norske Veritas (DNV) • Lloyds Register of Shipping (LRS) 	No No Yes No
standards, specifications, approvals Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
<ul style="list-style-type: none"> • total • during manufacturing • during operation • after end of life 	801.7 kg 18.9 kg 782.3 kg 0.27 kg
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> • during operation • during transport • during storage 	-25 ... +70 °C; with natural convection -40 ... +85 °C -40 ... +85 °C
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
connection method	
type of electrical connection	screw terminal
<ul style="list-style-type: none"> • at input • at output • for auxiliary contacts 	DC input, +, -, PE: 1 screw terminal each for 0.2 ... 6/4 mm ² single-core/finely stranded +, -: 2 screw terminals each for 0.2 ... 6/4 mm ² single-core/finely stranded Alarm signals: 2 screw terminals for 0.14 ... 1.5 mm ² single-core/finely stranded
mechanical data	
width × height × depth of the enclosure	90 × 125 × 125 mm
installation width × mounting height	90 mm × 225 mm
required spacing	
<ul style="list-style-type: none"> • top • bottom • left • right 	50 mm 50 mm 0 mm 0 mm
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
<ul style="list-style-type: none"> • DIN-rail mounting • S7 rail mounting • wall mounting 	Yes No No
housing can be lined up	Yes
net weight	1.2 kg
accessories	
mechanical accessories	Device identification label 20 mm × 7 mm, pale turquoise 3RT1900-1SB20
further information internet links	
internet link	
<ul style="list-style-type: none"> • to website: Industry Mall • to web page: selection aid TIA Selection Tool • to web page: power supplies • to website: CAx-Download-Manager • to website: Industry Online Support 	https://mall.industry.siemens.com https://www.siemens.com/tstcloud https://siemens.com/sitop https://siemens.com/cax https://support.industry.siemens.com
additional information	
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and

solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Classifications

	Version	Classification
eClass	14	27-04-07-01
eClass	12	27-04-07-01
eClass	9.1	27-04-07-01
eClass	9	27-04-07-01
eClass	8	27-04-90-02
eClass	7.1	27-04-90-02
eClass	6	27-04-90-02
ETIM	9	EC002540
ETIM	8	EC002540
ETIM	7	EC002540
IDEA	4	4130
UNSPSC	15	39-12-10-04

Approvals Certificates

General Product Approval



CB

[Manufacturer Declaration](#)

[Declaration of Conformity](#)



UK
CA



CE

EG-Konf.



UL

General Product Approval	Maritime application	Environment
--------------------------	----------------------	-------------



RCM



DNV
DNV



EPD

last modified:

4/4/2025 