

SIMATIC S7,
TD 200 TEXTDISPLAY FOR S7-200, 2 LINES,
WITH CABLE (2.5M) AND MOUNTING ACCESSORIES,
CONFIGURATION WITH STEP7-MICRO/WIN W/O ATEX
CERTIFICATE



Operator control and monitoring	
Operating/fault messages	
Number of lines	2
Number of characters per line	20 ; Characters/line: ASCII, cyrillic; 10 characters/line: Chinese
Character size	5 mm
Display	
Design of display	LCD backlit
Supply voltage	
Rated value (DC)	24 V ; Power supply via the S7-200 communications interface or optional external power supply unit; the CPU sensor power supply (24 V DC) is not subjected to load
Input current	
Rated value at 24 V DC	120 mA
Interfaces	
Point-to-point	
Transmission rate, max.	187.5 kbit/s
1. Interface	
Physics	RS 485
Functionality	

PPI	Yes
PPI	
Number of nodes, max.	126 ; S7-200, OP, TP, TBP, PG / PC
Degree and class of protection	
IP65	Yes ; at front
Ambient conditions	
Operating temperature	
min.	0 °C
max.	60 °C
Storage/transport temperature	
min.	-40 °C
max.	70 °C
Dimensions	
Width	148 mm
Height	76 mm
Depth	27 mm
Mounting cutout/device depth (W x H x D)	
Mounting cutout, width	138 mm
Mounting cutout, height	68 mm
Cabinet/switchboard thickness	0.3 mm ; 0.3 to 4 mm
Weights	
Weight, approx.	250 g
Status	Jul 21, 2014