



Figure similar

SIMATIC S7-300, Analog input SM 331, Isolated 8 AI, resolution 13 bits
U/I/resistor/Pt100, NI100, NI1000, LG-NI1000, PTC/KTY, 66 ms conversion time;
1x 40-pole

Input current	
from backplane bus 5 V DC, max.	90 mA
Power loss	
Power loss, typ.	0.4 W
Analog inputs	
Number of analog inputs	8
• For resistance measurement	8
permissible input voltage for voltage input (destruction limit), max.	30 V; 12 V continuous, 30 V for max. 1 s
permissible input current for current input (destruction limit), max.	40 mA
Input ranges	
• Voltage	Yes
• Current	Yes
• Thermocouple	No
• Resistance thermometer	Yes
• Resistance	Yes
Input ranges (rated values), voltages	
• 0 to +10 V	Yes
— Input resistance (0 to 10 V)	100 kΩ
• 1 V to 5 V	Yes
— Input resistance (1 V to 5 V)	100 kΩ
• 1 V to 10 V	No
• -1 V to +1 V	Yes
— Input resistance (-1 V to +1 V)	100 kΩ
• -10 V to +10 V	Yes
— Input resistance (-10 V to +10 V)	100 kΩ
• -2.5 V to +2.5 V	No
• -250 mV to +250 mV	No
• -5 V to +5 V	Yes
— Input resistance (-5 V to +5 V)	100 kΩ
• -50 mV to +50 mV	Yes
— Input resistance (-50 mV to +50 mV)	100 kΩ
• -500 mV to +500 mV	Yes
— Input resistance (-500 mV to +500 mV)	100 kΩ
• -80 mV to +80 mV	No
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
— Input resistance (0 to 20 mA)	100 Ω
• -10 mA to +10 mA	No

• -20 mA to +20 mA — Input resistance (-20 mA to +20 mA) • -3.2 mA to +3.2 mA • 4 mA to 20 mA — Input resistance (4 mA to 20 mA)	Yes 100 Ω No Yes 100 Ω
Input ranges (rated values), thermocouples	
• Type B • Type C • Type E • Type J • Type K • Type L • Type N • Type R • Type S • Type T • Type U • Type TXK/TXK(L) to GOST	No No No No No No No No No No No No
Input ranges (rated values), resistance thermometer	
• Cu 10 • Ni 100 — Input resistance (Ni 100) • Ni 1000 — Input resistance (Ni 1000) • LG-Ni 1000 — Input resistance (LG-Ni 1000) • Ni 120 • Ni 200 • Ni 500 • Pt 100 — Input resistance (Pt 100) • Pt 1000 • Pt 200 • Pt 500	No Yes; Standard/climate 100 MΩ Yes 100 MΩ Yes; Standard/climate 100 MΩ No No No Yes; Standard/climate 100 MΩ No No No
Input ranges (rated values), resistors	
• 0 to 150 ohms • 0 to 300 ohms • 0 to 600 ohms — Input resistance (0 to 600 ohms) • 0 to 6000 ohms — Input resistance (0 to 6000 ohms)	No No Yes 100 MΩ Yes 100 MΩ
Thermocouple (TC)	
Temperature compensation	
— parameterizable — internal temperature compensation — external temperature compensation with compensations socket	No No No
Characteristic linearization	
• parameterizable — for thermocouples — for resistance thermometer	Yes No yes; Pt100 standard/air con.; Ni100 standard/air con.; Ni1000 standard/air con.; LG-Ni1000 standard/air con.
Cable length	
• shielded, max.	200 m; max. 50 m at 50 mV
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max. • Integration time, parameterizable • Basic conversion time (ms) • Interference voltage suppression for interference frequency f1 in Hz	13 bit Yes; 60 / 50 ms 66 / 55 ms 50 / 60 Hz

Encoder			
Connection of signal encoders			
• for voltage measurement	Yes		
• for current measurement as 2-wire transducer	Yes; with external supply		
• for current measurement as 4-wire transducer	Yes		
• for resistance measurement with two-wire connection	Yes		
• for resistance measurement with three-wire connection	Yes		
• for resistance measurement with four-wire connection	Yes		
Errors/accuracies			
Operational error limit in overall temperature range			
• Voltage, relative to input range, (+/-)	0.6 %; ±0.6 % (±5 V, 10 V, 1 to 5 V, 0 to 10 V); ±0.5 % (±50 mV, 500 mV, 1 V)		
• Current, relative to input range, (+/-)	0.5 %; ±20 mA, 0 to 20 mA, 4 to 20 mA		
• Resistance, relative to input range, (+/-)	0.5 %; 0 to 6 kohms, 0 to 600 kohms		
• Resistance thermometer, relative to input range, (+/-)	1 Kelvin (Pt100, Ni100, climatic; Ni1000, LG-Ni1000, standard; Ni1000, LG-Ni1000, climatic); 1.2 Kelvin (Pt100, Ni100, standard)		
Basic error limit (operational limit at 25 °C)			
• Voltage, relative to input range, (+/-)	0.4 %; 0.4% (±5 V, 10 V, 1 to 5 V, 0 to 10 V); 0.3% (±50 mV, 500 mV, 1 V)		
• Current, relative to input range, (+/-)	0.3 %; ±20 mA, 0 to 20 mA, 4 to 20 mA		
• Resistance, relative to input range, (+/-)	0.3 %; 0 to 6 kohms, 0 to 600 kohms		
• Resistance thermometer, relative to input range, (+/-)	1 Kelvin (Pt100, Ni100, standard); 0.8 Kelvin (Pt100, Ni100, climatic; Ni1000, LG-Ni1000, standard; Ni1000, LG-Ni1000, climatic)		
Interrupts/diagnostics/status information			
Diagnostics function	No		
Alarms			
• Diagnostic alarm	No		
• Limit value alarm	No		
Diagnoses			
• Diagnostic information readable	No		
Diagnostics indication LED			
• Group error SF (red)	No		
Potential separation			
Potential separation analog inputs			
• between the channels	No		
• between the channels and backplane bus	Yes		
Isolation			
Isolation tested with	500 V DC		
connection method			
required front connector	40-pin		
Dimensions			
Width	40 mm		
Height	125 mm		
Depth	117 mm		
Weights			
Weight, approx.	250 g		
Classifications			
		Version	Classification
	eClass	14	27-24-22-01
	eClass	12	27-24-22-01
	eClass	9.1	27-24-22-01
	eClass	9	27-24-22-01
	eClass	8	27-24-22-01
	eClass	7.1	27-24-22-01
	eClass	6	27-24-22-01
	ETIM	9	EC001420
	ETIM	8	EC001420
	ETIM	7	EC001420
	IDEA	4	3562
	UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval



[Manufacturer Declaration](#)

[Miscellaneous](#)



[Metrological Approval](#)

General Product Approval	EMV	For use in hazardous locations
--------------------------	-----	--------------------------------



[FM](#)

For use in hazardous locations	Marine / Shipping
--------------------------------	-------------------



[Miscellaneous](#)

[CCC-Ex](#)



Marine / Shipping



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

last modified: 4/7/2025