



Figure similar

SIMATIC S7-300, Connection IM 360 in central rack for connection of max. 3 expansion racks, with C-bus

| Input current                      |        |
|------------------------------------|--------|
| from backplane bus 5 V DC, max.    | 350 mA |
| Power loss                         |        |
| Power loss, typ.                   | 2 W    |
| Hardware configuration             |        |
| Number of interfaces per CPU, max. | 1      |
| Dimensions                         |        |
| Width                              | 40 mm  |
| Height                             | 125 mm |
| Depth                              | 120 mm |
| Weights                            |        |
| Weight, approx.                    | 225 g  |
| Classifications                    |        |

|        | Version | Classification |
|--------|---------|----------------|
| eClass | 14      | 27-24-22-08    |
| eClass | 12      | 27-24-22-08    |
| eClass | 9.1     | 27-24-22-08    |
| eClass | 9       | 27-24-22-08    |
| eClass | 8       | 27-24-22-08    |
| eClass | 7.1     | 27-24-22-08    |
| eClass | 6       | 27-24-22-08    |
| ETIM   | 9       | EC001423       |
| ETIM   | 8       | EC001423       |
| ETIM   | 7       | EC001423       |
| IDEA   | 4       | 3564           |
| UNSPSC | 15      | 32-15-17-05    |

| Approvals / Certificates |     |
|--------------------------|-----|
| General Product Approval | EMV |



[Manufacturer Declaration](#)



For use in hazardous locations



[FM](#)



[Miscellaneous](#)

For use in hazard-  
ous locations

Marine / Shipping

[CCC-Ex](#)



[NK / Nippon Kaiji Ky-  
okai](#)

Marine / Shipping



[CCS \(China Classifica-  
tion Society\)](#)

last modified:

4/7/2025