



Figure similar

SIMATIC S7-300, Connection IM 361 in expansion rack for connection to central rack (IM360), supply voltage 24 V DC, with C-bus

Supply voltage			
Rated value (DC)			
• 24 V DC		Yes	
Input current			
from supply voltage L+, max.		500 mA	
Power loss			
Power loss, typ.		5 W	
Hardware configuration			
Number of interfaces per CPU, max.		3	
Dimensions			
Width		80 mm	
Height		125 mm	
Depth		120 mm	
Weights			
Weight, approx.		505 g	
Classifications			
		Version	Classification
	eClass	14	27-24-22-08
	eClass	12	27-24-22-08
	eClass	9.1	27-24-22-08
	eClass	9	27-24-22-08
	eClass	8	27-24-22-08
	eClass	7.1	27-24-22-08
	eClass	6	27-24-22-08
	ETIM	9	EC001423
	ETIM	8	EC001423
	ETIM	7	EC001423
	IDEA	4	3564
	UNSPSC	15	32-15-17-05

Approvals / Certificates	
General Product Approval	EMV



For use in hazardous locations



[FM](#)



[Miscellaneous](#)

For use in hazardous locations	Marine / Shipping
--------------------------------	-------------------

[CCC-Ex](#)



[NK / Nippon Kaiji Kyokai](#)

Marine / Shipping



[CCS \(China Classification Society\)](#)

last modified:

4/7/2025