

SIMATIC S7-200, USB/PPI cable MM MULTIMASTER, for connection of S7-200 to USB PC interface, no Freeport support, length: 5.6 m, scope of supply: 1 USB/PPI cable



General information			
Product type designation	USB/PPI multi-master		
Supply voltage			
Design of the power supply	From USB interface		
Interfaces			
Point-to-point connection			
• Transmission rate, max.	187.5 kbit/s; 9.6 / 19.2 / 187.5 kbit/s; setting: not necessary		
Protocols			
PPI	Yes; 10/11 bit		
Interrupts/diagnostics/status information			
LED status display	Tx (green): USB send display; Rx (green): USB receive display; PPI (green): RS-485 send display		
Potential separation			
Potential separation exists	Yes		
Cables			
Cable length	5.63 m		
Weights			
Weight, approx.	300 g		
Classifications			
		Version	Classification
	eClass	14	27-24-22-20
	eClass	12	27-24-22-20
	eClass	9.1	27-24-22-20
	eClass	9	27-24-22-20
	eClass	8	27-24-92-05
	eClass	7.1	27-24-92-05
	eClass	6	27-24-92-05
	ETIM	9	EC000237
	ETIM	8	EC000237
	ETIM	7	EC000237
	IDEA	4	3553
	UNSPSC	15	32-15-17-03
Approvals / Certificates			
General Product Approval		For use in hazardous locations	



[Miscellaneous](#)



[FM](#)



For use in hazardous locations

[CCC-Ex](#)

last modified:

3/12/2024 