



Front connector (D 2X8I/O) S7-300 Screw

Front connector module with flat ribbon Cable connection for digital 16 I/O modules of the S7-300, Power supply over Screw terminal

target system	SIMATIC S7-300
suitability for use	Digital I/O modules
product type designation	Fully modular connection
product designation	Front connector module
Operating data / header	
operating voltage / at DC	
• rated value	24 V
• lue	60 V
• maximum	60 V
current / rated value	1 A
continuous current / at DC / per plug-in contact / maximum	1 A
total current / maximum	4 A
operating temperature	0 ... 60 °C
ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
number of poles	20; of the front connector
manufacturer's article number / of device connector / usable	replacement for S7-300 20 pole
number of the plug contacts / of the electrical connection	2
type of electrical connection / for connecting cable	Plug-in connection
number of poles / at the 1st interface	16; the IDC connector for the connection cable
position / of the terminal	at the top
type of electrical connection / for power supply	Screw-type terminal
number of terminals	4; 2 x 1 x L+, 2 x 1 x M
width of screwdriver blade	3.5 mm
tightening torque / with screw-type terminals	0.4 ... 0.7 N·m
product component / required / end cover plate	No
number of cables / per connection	2; Connection for internal system: Combination of 1 or 2 Wires until the sum total of cross sections be achieved in a ferrule.
stripped length	6 mm
type of connectable conductor cross-sections / solid	No
connectable conductor cross-section	
• for flexible conductor / with core end processing	0.25 ... 1.5 mm²; End sleeve according to DIN 46228 without plastic collar
• stranded	0.25 ... 1.5 mm²
• finely stranded / without core end processing	0.25 ... 1.5 mm²
• finely stranded / with core end processing	0.25 ... 1.5 mm²
type of wire end sleeve	
• without plastic sleeve / according to DIN 46228-1	Length 5mm to 7mm
outer diameter / of the wire insulation	3.1 mm; to the connection of the supply terminal
wire length / maximum	30 m; between front connector module and terminal module

General data / header	
mounting type	direct mounting
degree of pollution	2
overvoltage category	2
design tested acc. to type of protection / EEx e	No
certificate of suitability / cULus approval	Yes
reference code / according to IEC 81346-2	XG
material / of the insulating body	other
color / of the enclosure	black
product feature / transparent	No
net weight	0.099 kg

last modified:

4/9/2025 